

se2thesis—A Thesis Class for the Chair of Software Engineering II at the University of Passau, Germany*

Stephan Lukasczyk[†]

Released 2026-04-03

Abstract

One can choose from a wide variety of templates to write a thesis. Many universities provide very rigorous style guides and force their students to obey to those guides, even though they might be questionable from a typography point of view. Other universities do not provide such guides and leave it to their students to choose or come up with a template. The latter is causing very differently-looking theses.

To avoid such a situation in the future this bundle combines several \LaTeX packages and classes for the use at the Chair of Software Engineering II at the University of Passau. We provide, among others, a document class for theses that shall be used by our students. The bundle is designed in a way that one can use the basic components as standalone packages to allow their reuse for other projects.

Contents

I	User Documentation	1
1	Introduction	1
1.1	Installation	1
1.2	Availability on Overleaf	2
1.3	Availability in MonsterWriter	2
1.4	General Macros	2
2	License	2
3	The se2thesis class	2
3.1	Load-time options	3
3.2	The title page	4
3.3	Type-area settings	5
3.4	Abstract for the thesis	5
3.5	Acknowledgements	6
3.6	Document structuring	6
3.7	Authorship declaration	6
3.8	Research Questions and findings summaries	7
3.9	Language Support and Hyphenation	7

*This file describes v4.4.1, last revised 2026-04-03.

[†]E-mail: stephan@dante.de

4	The se2colors package	8
5	The se2fonts package	10
6	The se2packages package	11
6.1	The Recommended Packages	11
6.1.1	Quoting with csquotes	11
6.1.2	Number formatting with siunitx	11
6.1.3	Code Listings	11
6.1.4	Designing Tables	12
6.1.5	Controlling Ligatures, Orphans, and Widows	12
6.1.6	Use microtype for Microtypographic Optimisation	12
6.1.7	Use biblatex for Bibliographic References	13
6.1.8	Use cleveref for Internal References	13
6.2	Loading se2packages	13
6.3	Additional Recommended Packages	15
II	Implementation	16
1	Global helpers	17
2	The se2thesis implementation	17
2.1	Define Variables	18
2.2	Load-time options	19
2.3	Package loading	20
2.4	User macros for the title page	21
2.5	Define logo, paper size, and paper style	22
2.6	The title page	24
2.7	Styling of the sectioning commands	29
2.8	Provide an environment for abstracts	30
2.9	Provide an environment for acknowledgements	31
2.10	Document structuring macros	31
2.11	Declaration of authorship	32
2.12	Research questions and summary boxes	33
3	Translations for se2thesis	34
3.1	English Translations	34
3.2	German Translations	34
4	se2colors implementation	36
4.1	Load-time options	36
4.2	Option handling	36
4.3	Colour definitions	37
5	se2fonts implementation	39
5.1	Load-time options	39
5.2	Helper macros	39
5.3	Font loading	40

6	se2packages implementation	41
6.1	Load-time options	41
6.2	Option handling	43
6.3	Package loading	43
	Index	48

Part I

User Documentation

The first part of this file provides the documentation for the user of the se2thesis bundle. We provide the implementation in the second part of this document, starting at page 16, for those who are curious.

1 Introduction

The University of Passau does not provide a common thesis template to its students. For theses, written at the Chair of Software Engineering II, many students chose between two templates that were provided by different people from the chair; other students chose from the large variety of templates available from the internet, causing each thesis looking differently.

The author of this package provided a template, which he initially created for his bachelor's and master's thesis, that was recommended and used by many students. The implementation of that template, however, was very hacky and required some changes over time. This led to the idea of creating a new template from scratch, that shall be used by all our students for their various types of theses, from bachelor to PhD level. The result is the se2thesis bundle.

The bundle itself consists of several L^AT_EX classes and packages that also allow reuse of various parts of it. Its main class is the se2thesis document class, an extension of the KOMA-Script scrbook document class. The packages se2colors and se2fonts provide necessary colour and font settings for the se2thesis class; the se2packages allows to load several recommended packages (see Section 6) with our recommended, predefined settings. They are available as separate packages, however, to allow their reuse for other classes, packages, and projects, as well.

1.1 Installation

The se2thesis bundle is available from CTAN¹. It is part of both MiK_TE_X and T_EXLive. You can find its development version from GitHub². The easiest way of installing it is through your T_EX distribution; please check your distribution's documentation on this. Note that it might be necessary to update your T_EX distribution because they might not provide you updates; for example, there is a new version of T_EXLive every year which needs to be installed separately. If you have installed an older version of se2thesis consider updating it to the latest version available from CTAN through your distribution.

For manual installation, we recommend to clone the Git repository and run the l3build tool that we also use for building the bundle. Running l3build ctan builds the source files and compiles the documentation. This creates a folder build containing these artefacts; build/doc contains the documentation, build/local the source files. See the documentation of l3build and your T_EX distribution on how to install them manually. Please note that l3build also provides a l3build install target to install the bundle files to your local texmf tree.

The "Island of T_EX" project provides Docker images of T_EXLive³. If you do not want to install/update T_EXLive on your system you might want to consider their latest image, which contains a recent T_EXLive 2023 build. They build their images weekly, thus also recent releases of se2thesis will be part of the image soon after their release date.

¹ctan.org/pkg/se2thesis

²github.com/se2p/se2thesis

³islandoftex.gitlab.io/community/projects/docker/

1.2 Availability on Overleaf

Since April 3, 2024, the `se2thesis` document template is also available from Overleaf. The document that is in Overleaf's gallery is based on the example document that comes with this package. Any Overleaf user can just create a new thesis document based on the template by clicking the respective button on Overleaf's gallery page.

The gallery entry for `se2thesis` is available from <https://www.overleaf.com/latex/templates/se2thesis-a-thesis-class-for-the-chair-of-software-engineering-ii-at-the-university-of-passau-germany/fpymkxmxbgpc>.

Important remark: Currently, the Overleaf template does not support $\text{Lua}\text{\LaTeX}$ but requires builds with $\text{pdf}\text{\LaTeX}$. The reason is that Overleaf does not yet ship \TeX Live 2024, but only \TeX Live 2023, which does not provide the respective font package (notably `inconsolata-nerd-font`). Until the latest \TeX Live will be available from Overleaf, one can only use the $\text{pdf}\text{\LaTeX}$ mode, which has some drawbacks on the fonts, but works fine otherwise. From the Overleaf blog, we assume that \TeX Live 2024 might be available from some time in autumn 2024. We will update this documentation accordingly, as soon as the new version is available.

1.3 Availability in MonsterWriter

Since October 2024, `se2thesis` is also part of `MONSTERWRITER`, a graphical tool that assists students to write academic papers. The `MONSTERWRITER` GUI allows to focus on the content of a work and allows to export it in various common publisher styles and formats.

The `MONSTERWRITER` website monsterwriter.com provides more details on the tool, and a YouTube video (youtu.be/BWOumwmh18g) demonstrates some of the features of their `se2thesis` integration.

1.4 General Macros

They all have in common one macro, `\IfFormatAtLeastTF`; this macro is part of the latest \LaTeX kernel. However, not all users might have upgraded their \TeX installation to a level using a recently-enough kernel version. Therefore, every class and package of this bundle will conditionally define the following macro:

<code>\IfFormatAtLeastTF</code>	<code>\IfFormatAtLeastTF {<version>} {<then block>} {<else-block>}</code>
---------------------------------	---

Checks whether the used \LaTeX format is at least the one from the given date value. The date needs to be specified either in `YYYY/MM/DD` or in `YYYY-MM-DD` format.

2 License

Permission is granted to copy, distribute, and/or modify this software under the terms of the \LaTeX Project Public License (LPPL), version 1.3c or later (<https://www.latex-project.org/lppl.txt>). The software has the status 'maintained'.

3 The `se2thesis` class

The `se2thesis` class is the central component of this bundle. It provides a wide variety of settings, mostly regarding the title page (see Section 3.2) and the type area (see Section 3.3).

We aim to keep the `se2thesis` class relatively small, especially considering packages that we load. Currently, the class itself loads the `se2colors` (see Section 4) and `se2fonts` (see Section 5)

packages. The following packages and classes are loaded: `expl3`, `l3keys2e` in case one uses a \LaTeX kernel from before 2022-06-01, `graphicx`, `translations`, `KOMA-Script`, `xcolor`, `ifthen`, as well as `fontspec`, `unicode-math`, `inconsolata-nerd-font` and `libertinus-otf` if one uses \LuaTeX ; for \pdfLaTeX we load `fontenc`, `libertinus-type1`, and `inconsolata` instead of the latter three. Furthermore, we load `microtype`; when using \LuaTeX , we also load `lua-widow-control` and `selnolig`.

However, we recommend to use a couple of further packages, together with some further options to those package. We describe these settings in Section 6. Please consider looking at this section when starting to write your document.

Before we start with a detailed documentation of the class, we explain one helper macro that can be used to check whether a package has been loaded.

<code>\slcd_package_if_loaded_p:n</code>	★ <code>\slcd_package_if_loaded:nTF {<package name>} {<true code>} {<false code>}</code>
<code>\slcd_package_if_loaded:nTF</code>	★ Checks whether a package has been loaded and conditionally executes code.

Updated: 2022-09-27

3.1 Load-time options

The `se2thesis` class defines several load-time options, all of them optional, on top of the options provided by the `KOMA-Script` document classes.

<code>class</code>	<code>class = <choice></code>
--------------------	-------------------------------------

Set the base document class. Values are `scrreprt` or `scrbook`. *Note:* you cannot use `scartcl` because it does not provide the required chapter sectioning. Default is `scrbook`.

Please note that if you want to have the bibliography numbered or use an appendix with alpha-numbering (A, B, ...), you want to explicitly use `scrreprt` as the base class; for some (currently unknown) reason this does not work with the default `scrbook`.

<code>paper</code>	<code>paper = <choice></code>
--------------------	-------------------------------------

Set the paper format. Possible values are `a4` or `b5`. Default is `a4`.

<code>logfile</code>	<code>logfile = {<path-to-file>}</code>
----------------------	---

Defines the path to the University's logo for the title page.

<code>thesistype</code>	<code>thesistype = <choice></code>
-------------------------	--

Defines the type of the thesis. Possible values are: `bachelor` for a bachelor's thesis, `bachelorproposal` for a proposal to a bachelor's thesis, `master` for a master's thesis, `masterproposal` for a proposal to a master's thesis, `phdproposal` for a proposal to a PhD thesis, `phd` for a PhD thesis in the natural sciences, `phdeng` for a PhD thesis in engineering, and `phdphil` for a PhD thesis in natural philosophy.

<code>colormode</code>	<code>colormode = <choice></code>
------------------------	---

Select the color scheme used by the automatically loaded `se2colors` package, see Section 4 for a description.

3.2 The title page

Designing a title package for a thesis can be complicated. There might be some requirements that are not obvious to the user, especially considering the positioning of elements. The University of Passau, for example, requires the logo to be positioned on the top right of a page; theses—especially PhD theses that shall be published through the University’s library system—could be rejected from publication by the library until this is fixed.

We thus redeclare the standard `\maketitle` macro from KOMA-Script and customise it to our needs.

<hr/> <code>\@maketitle</code>	<code>\@maketitle</code>
	We override the definition of the <code>\@maketitle</code> macro for our needs. In addition to the macros provided by the KOMA-Script classes for the title-page values (e.g. <code>\author</code> , <code>\title</code>), we provide some further macros that can be used. Setting values to these macros is optional in any case, if they are not set, the corresponding value is not put to the title page.
<hr/> <code>\version</code>	<code>\version {<version>}</code>
	Specify the version of the document. This can, for example, be a git hash of the current version.
<hr/> <code>\degreeprogramme</code>	<code>\degreeprogramme {<programme-name>}</code>
	Specify the degree programme the thesis is meant to be accepted in. Possible values are, among others, ‘Informatik’ if you are writing your thesis in German, or ‘Computer Science’ if you are writing the thesis in English.
<hr/> <code>\matrnumber</code>	<code>\matrnumber {<matriculation-number>}</code>
	Specify the matriculation number of the student writing the thesis. This is required for bachelor’s and master’s theses.
<hr/> <code>\supervisor</code> <hr/> <code>\cosupervisor</code>	<code>\supervisor {<name>}</code> <code>\cosupervisor {<name>}</code>
	Specify the name of your supervisor and co-supervisor. Both people usually are professors.
<hr/> <code>\advisor</code> <hr/> <code>\coadvisor</code>	<code>\advisor {<name>}</code> <code>\coadvisor {<name>}</code>
	Specify the name of your advisor and co-advisor. Both people usually are PhD students or postdocs.
<hr/> <code>\department</code> <hr/> <code>\institute</code>	<code>\department {<name>}</code> <code>\institute [{<short-name>}] {<name>}</code>
	Specify the department and institute. The department is, for example, ‘Faculty of Computer Science and Mathematics’, the institute, for example, ‘Chair of Software Engineering II’. If the <code>\department</code> value is not specify, we use ‘Faculty of Computer Science’ as the default value for English theses and ‘Fakultät für Informatik und Mathematik’ as the default value of German theses.
<hr/> <code>\external</code>	<code>\external {<name>}</code>
	Specify the name of an external referee.

`\location` `\location {⟨name-of-town⟩}`

Specify the name of your residence town for the signature field.

To define the path to the logo graphics we require a different workflow: We do not bundle logo graphics with this package due to legal restrictions. They can be downloaded from the University’s website; please note that the website for downloading the logo graphics is only accessible from within the University’s campus network or a VPN connection. To specify the path to the logo graphics, we provide a load-time option to the `se2thesis` class called `logfile` (see Section 3.1).

When printing the thesis in two-side mode—which we recommend—the back of the title page again denotes author and title on the bottom.

`\@lowertitleback` `\l@lowertitleback`

Override this internal macro of KOMA-Script to print this information on the back side of the title page.

Additionally, we provide some internal rewritings to standard macros from KOMA-Script that allow to automatically split authors using the `\and` command.

`\author` `\author {⟨author⟩}`

`\@author` We rewrite the definitions of `\author` and `\@author` to do this splitting automatically. Additionally, this also adds a correctly translated version of ‘and’ between the author names if required.

3.3 Type-area settings

The `se2thesis` class manipulates the type area compared to the default settings of the KOMA-Script classes. Our settings are inspired by the `classicthesis` package, which itself is inspired by the style used by famous statistician Edward Tufte. We provide predefined settings for DIN-A4, DIN-A5, and DIN-B5 papers. If you need settings for other paper sizes, please open an issue on this package’s GitHub repository (<https://github.com/se2p/se2thesis>) and we will happily include those settings in a future release of this bundle.

Additionally, we are setting the page footer in a way that it contains the page numbers in the outer margin and the headmarks split from the page numbers by a vertical bar.

3.4 Abstract for the thesis

Each thesis shall come with an abstract that summarises its content. The abstract should be written in the language the thesis is written in. Additionally, there is the requirement to provide a German abstract if the thesis is written in a foreign language.

`\abstract` `\abstract`

We ensure that the `\abstract` command is defined for all document classes.

`abstract (env.)` To typeset an abstract, we provide an environment called `abstract`. The environment takes an optional argument that specifies the language that is used in this abstract. Setting the abstract’s language will cause its title to change to the respective language; additionally, hyphenation is also changed for that language.

```
\begin{abstract}[language]
  Your abstract text.
\end{abstract}
```


3.5 Acknowledgements

`acknowledgements (env)` We provide the acknowledgements environment to typeset acknowledgements for your thesis. Using this environment is optional. Usually, bachelor's and master's thesis do not contain such an acknowledgements section, however, there is no general rule to this.

```
\begin{acknowledgements}[language]
  Your acknowledgements.
\end{acknowledgements}
```

3.6 Document structuring

A larger work, such as a thesis, is usually structured in three large blocks: a frontmatter that provides all the overview, such as abstract, table of contents, etc., a mainmatter that contains all the actual content, and a backmatter for appendices. `se2thesis` ensures that the following macros are defined because they are not provided by all KOMA-Script classes.

<code>\frontmatter</code>	<code>\frontmatter</code>
<code>\mainmatter</code>	<code>\mainmatter</code>
<code>\backmatter</code>	<code>\backmatter</code>

Switches between frontmatter, mainmatter, and backmatter. Most notably, the frontmatter will have roman page numbers, while the other two will have arabic page numbers.

3.7 Authorship declaration

The University of Passau requires its students to provide an authorship declaration as part of their thesis for submission. They provide a template form, which would not fit the style of the `se2thesis` class. Thus, we provide the `\authorshipDeclaration` macro to typeset such a declaration. It uses the original (German) text of the declaration and fills in the values that are specified by the `\author` and `\location` macros.

<code>\authorshipDeclaration</code>	<code>\authorshipDeclaration</code>
-------------------------------------	-------------------------------------

Print the authorship declaration text.

Please note: the authorship declaration will always be printed in German, no matter what the language of the thesis is. This happens due to legal requirements. In order to make this work, you have to load the `babel` or `polyglossia` package in a way that it also supports German hyphenation. For example, use

```
\usepackage[ngerman,main=UKenglish]{babel}
```

for a thesis with *traditional English*⁴ as its main language and support for German.

<code>\signatureBox</code>	<code>\signatureBox</code> [<i>width</i>] { <i>signature-name</i> }
----------------------------	---

A helper macro to print the signature box for the authorship declaration. The optional argument [*width*] allows to specify a custom width for the signature line. The default is 5 cm. The mandatory argument {*signature-name*} specifies the name of the signee, which will be typeset below the signature line.

⁴there is a nice, probably photoshopped, picture of a Steam setup dialogue stating that American English is a 'simplified version' of British English, see <https://jakubmarian.com/is-american-english-simplified-and-british-english-traditional/>.

3.8 Research Questions and findings summaries

Most theses written at our Chair will require the student to provide some empirical evaluation of their work to shed insights whether their proposed ideas are actually useful. For an empirical study, one needs to specify research questions and maybe also hypotheses. The `se2thesis` class supports this by providing environments for this.

- `resq (env.)` The `resq` environment shall be used to specify a research question.
- `hyp (env.)` The `hyp` environment shall be used to specify a hypothesis.
- `summary (env.)` After describing the results, we recommend to give an explicit summary of the findings for a research question or hypothesis. This summary shall be given in one or two sentences. The `summary` environment provides a convenient way for this; it will be typeset in a highlighted box that is easy to spot and also allows readers of the work to quickly grasp the main findings.

```
\begin{summary}[label-reference]
  The summary text itself.
\end{summary}
```

The environment expects as a parameter a label, for example, to a research question; however, this can also be arbitrary text.

3.9 Language Support and Hyphenation

The study regulations of the University of Passau require students to write their thesis in either German or English. For both cases it is recommended to load a package for the correct hyphenation patterns. Usually, one can either choose between the `babel` and `polyglossia` package. For a detailed discussion in the differences and which to choose, please use the search engine of your choice.

For this documentation we stick with the `babel` package, which is often considered to be the standard package.

If you write your thesis in German, load `babel` in your preamble like follows

```
\usepackage[ngerman]{babel}
```

For a thesis in English, you have to also load the German variant plus the English one as the default (see Section 3.7 for an explanation)

```
\usepackage[ngerman,main=UKenglish]{babel}
```

Note that by default, \LaTeX does not provide hyphenation for compound words, which is explained in the \TeX Book [2, p. 454] and a StackExchange post⁵. The `babel` package provides a way (called shorthands) for German, which allows to reenables hyphenation for compound words (as they are common on German). These shorthands are by default not available for English, but they can easily be added by adding

```
\usesshorthands{"}
\addto\extrasUKenglish{\languagesshorthands{ngerman}}
```

after loading `babel` with the aforementioned `\usepackage` macro⁶.

Please note: loading the `hyphenat` package is strongly discouraged by the `se2thesis` maintainer because it conflicts with the `hyp` environment provided by `se2thesis` (see Section 3.8).

⁵<https://tex.stackexchange.com/a/63234/14622>

⁶see <https://tex.stackexchange.com/a/298844/14622>

4 The se2colors package

Several colours are specific to the university and we want to have a comprehensive interface to access them throughout all our packages.

The se2colors package provides this exact features. One can load it using `\usepackage{se2colors}` in the document preamble.





<code>cmode</code>	<code>cmode = <choice></code>
Updated: 2022-11-03	Selects the colour mode that shall be used for creating the results, a choice from the options specified in Table 1. The default setting is 4C.

Table 1: Options provided by se2colors.

























Option	Description
<code>cmode=4C</code>	Define colours in CMYK colour space (<i>default</i>).
<code>cmode=CMYK</code>	Alias for the previous.
<code>CMYK</code> , <code>cmyk</code>	Aliases for the previous.
<code>cmode=RGB</code>	Define colours in RGB colour space.
<code>RGB</code> , <code>rgb</code>	Aliases for the previous.
<code>cmode=BW</code>	Define colours in black-and-white colour space.
<code>cmode=1C</code>	Alias for the previous.
<code>gray</code>	Alias for the previous.





































We define two basic colours that are taken from the University's logo, namely UPSE2-Gray  and UPSE2-Orange .

Additionally, we define four colours for the four faculties of the University:

- the Faculty of Law UPSE2-JUR ,
- the School of Business, Economics and Information Systems UPSE2-WIWI ,
- the Faculty of Arts and Humanities UPSE2-PHIL , and
- the Faculty of Computer Science and Mathematics UPSE2-FIM .

Finally, we define a full set of supplementary colours:

- UPSE2-DarkGray  with its derivatives
UPSE2-DarkGray1 , UPSE2-DarkGray2 , UPSE2-DarkGray3 , UPSE2-DarkGray4 , and
UPSE2-DarkGray5 .
- UPSE2-White  with its derivatives
UPSE2-White1 , UPSE2-White2 , UPSE2-White3 , UPSE2-White4 , and UPSE2-White5 .
- UPSE2-MediumGray  with its derivatives
UPSE2-MediumGray1 , UPSE2-MediumGray2 , UPSE2-MediumGray3 , UPSE2-MediumGray4 , and UPSE2-MediumGray5 .
- UPSE2-LightGray  with its derivatives
UPSE2-LightGray1 , UPSE2-LightGray2 , UPSE2-LightGray3 , UPSE2-LightGray4 ,
and UPSE2-LightGray5 .

- UPSE2-Orange  with its derivatives
UPSE2-Orange1 , UPSE2-Orange2 , UPSE2-Orange3 , UPSE2-Orange4 , and UPSE2-Orange5 .
- UPSE2-LightRed  with its derivatives
UPSE2-LightRed1 , UPSE2-LightRed2 , UPSE2-LightRed3 , UPSE2-LightRed4 , and UPSE2-LightRed5 .
- UPSE2-DarkRed  with its derivatives
UPSE2-DarkRed1 , UPSE2-DarkRed2 , UPSE2-DarkRed3 , UPSE2-DarkRed4 , and UPSE2-DarkRed5 .
- UPSE2-Green  with its derivatives
UPSE2-Green1 , UPSE2-Green2 , UPSE2-Green3 , UPSE2-Green4 , and UPSE2-Green5 .
- UPSE2-Blue  with its derivatives
UPSE2-Blue1 , UPSE2-Blue2 , UPSE2-Blue3 , UPSE2-Blue4 , and UPSE2-Blue5 .
- UPSE2-AccentGray  with its derivatives
UPSE2-AccentGray1 , UPSE2-AccentGray2 , UPSE2-AccentGray3 , UPSE2-AccentGray4 , and UPSE2-AccentGray5 .

5 The se2fonts package

The se2fonts package sets the fonts of the document. In the first version of the bundle, we were running to use Hermann Zaph’s *Palatino*, *Helvetica*, and *Neo Euler* fonts. However, we figured out that they are not part of a standard L^AT_EX installation, and thus required manual work by the user to install them. Furthermore, loading the fonts did not always work in a correct way.

Thus, we decided to rethink this decision and—as a consequence—now use different fonts that are part of a recent standard L^AT_EX installation: we use the *Libertinus* fonts⁷ for serif, sans-serif, and math typesetting and the *Inconsolata* font⁸ as a monospaced font.

Please note: this change might affect the way your documents look, and also might affect paragraph and line breaks!

If you are using Lua_T_EX, fonts are expected to be present as open-type fonts; using pdf_L_AT_EX will fallback to Type-1 fonts.

Please note: the package does not support X_YL_AT_EX!

The following options are defined by the se2fonts package to influence the selection of the fonts.

The following list provides examples for each of the fonts:

- An example text in Libertinus Serif
- An example text in Libertinus Sans
- An example text in Inconsolata

The package provides additional helper functions that are also available to the user.

<code>\pdftexengine</code>	<code>\pdftexengine</code>
<code>\xetexengine</code>	<code>\xetexengine</code>
<code>\luatexengine</code>	<code>\luatexengine</code>

These commands alias the built-in L^AT_EX3 macros `\sys_if_engine_pdftex_p:`, `\sys_if_engine_xetex_p:`, and `\sys_if_engine_luatex_p:`. They can be used to check which engine the user is currently running.

<code>\ifengineTF</code>	<code>\ifengineTF {<engine>} {<then block>} {<else block>}</code>
<code>\ifengineT</code>	<code>\ifengineT {<engine>} {<then block>}</code>
<code>\ifengineF</code>	<code>\ifengineF {<engine>} {<then block>}</code>

Allows to execute code based on the running engine. The base variant `\ifengineTF` expects the user to specify a condition, which can be built of combinations of the `\pdftexengine`, `\xetexengine`, and `\luatexengine` macros, followed by the code that will be executed if the condition holds and the code that will be executed if the condition does not hold.

For convenience, we provide the variants `\ifengineT` and `\ifengineF` that allow to omit an empty then or else branch, respectively.

⁷<https://github.com/alquier/libertinus>

⁸<http://levien.com/type/myfonts/inconsolata.html>

6 The se2packages package

Several packages can be useful for writing a thesis. We provide a simple package for the user that loads these support packages with the recommended options. Please note that you might not need all these packages, however, having a look at them (especially their documentation) might give you an insight whether to use a certain package. Our general recommendation is to use as few packages as you can; some might have conflicts, others basically do the same, or are outdated. Please consider reading the documentation of each package you are using to figure out whether they have any conflicts with other packages (for example, one cannot use the recommended siunitx package together with Slunits) or they might require to be loaded at special places in your preamble (for example, hyperref is usually meant to be loaded as the last package, except you are also using cleveref, which needs to be loaded *after* hyperref).

6.1 The Recommended Packages

We first present the packages we recommend and give a rationale why we believe they should be used. Afterwards, we will discuss how to load the se2packages package to use one or the other of these recommended packages in the next section.

6.1.1 Quoting with csquotes

The csquotes packages allows you for intelligent quoting of text. While verbose quotes are not that common in computer science, the package still provides some useful macros to the user.

6.1.2 Number formatting with siunitx

While siunitx's original purpose was to format physical quantities, it provides a lot of useful features when typesetting theses (and other documents) in computer science. When you skim through its documentation, especiall look at the \qty and \num macros, as well as the section on typesetting tabular material. We also recommend reading an extensive discussion on number formatting, precision of presented numbers, and more related topics in Beyer et al.'s journal paper on requirements and solutions for reliable benchmarking [1].

6.1.3 Code Listings

We prefer using the minted package for code listings because it provides a lot of options for styling as well as built-in support for a huge number of languages. However, this package requires the installation of Python and the setting of the -shell-escape option to your T_EX engine. Please read the package's documentation to set it up; the aforementioned Docker images from the Island of T_EX project provide you everything set up already.

In case you do not want to use the minted package, please consider using listings for typesetting your code listings.

Please be aware to use *either* minted *or* listings!

Attention: The way how minted is implemented causes the resulting code to be typeset in gray scale, if you use the se2colors package with option cmode=bw or the se2thesis class with colormode=bw (or their respective aliases). Students were requesting that they want to use the black-and-white mode of se2color because it saves lots of money when printing their thesis, while they want the colours in the syntax highlighting of minted. One can achieve this by adding hooks to the preamble of the document, after loading the minted package (which is recommend by setting minted=true as an option to se2packages):

```
\AddToHook{env/minted/begin}{\selectcolormodel{cmyk}}
\AddToHook{cmd/mintinline/before}{\selectcolormodel{cmyk}}
```

Thanks to Ulrike Fischer for pointing out this hook mechanism.⁹

Another option, if you do not want colours in the minted output when you use the grayscale mode of `se2colors` is the change the highlighting style, `minted` uses. The package for this provides the macro `\usemintedstyle`, which accepts a style available in your local `pygments` installation, see the `pygments` documentation¹⁰ for an overview over the available styles; the `bw` style is explicitly designed for this kind of scenario.

6.1.4 Designing Tables

A basically mandatory package to all users of tables is the `booktabs` package. Especially its documentation is a must-read! It provides a large variety of hints for designing tables, most notably that one should never ever use vertical lines; horizontal lines should be used sparsely; `booktabs` provides three macros for lines that shall be used instead of `\hline` from standard \LaTeX : `\toprule` for a rule on the top of a table, above the column heads; `\midrule` to separate column heads and the content, and `\bottomrule` to mark the bottom of a table. We highly recommend that you follow this style when writing your thesis.

Note that captions of tables shall be put *above* the table whereas captions of figures shall go *below* the figure. The rationale is that a figure should be more or less self explaining while a table almost always needs some explanation.

Unfortunately, the distances when using a `\caption` above a table are wrong by default; when creating tables, consider loading the `hvfloats` package and use its `\tabcaption` instead of `\caption` for tables. The `hvfloats` package furthermore provides additional useful macros to typeset all kinds of floats.

6.1.5 Controlling Ligatures, Orphans, and Widows

When using \LaTeX (which we recommend anyway), we additionally recommend to use the `selnolig` and `lua-widow-control` packages. The former implements a better control over ligatures, the latter provides better control over orphans and widows.

For some reason we were not yet able to fix properly, `lua-widow-control` works on some machine but fails on others, although they are using the same version of \TeX Live. We therefore deactivate `lua-widow-control` by default.

6.1.6 Use `microtype` for Microtypographic Optimisation

`microtype` is a game changer when writing documents. While standard \LaTeX provides reasonably good typography, the `microtype` package brings it to the next level. We refer you to the documentation of the package for details.

Additionally, we prefer to have a thin space around the m-dash. Although we are aware of the discussion whether to have such a space in English, we think it looks more beautiful and thus recommend it.

⁹tex.stackexchange.com/a/718719/14622

¹⁰pygments.org/styles/

6.1.7 Use biblatex for Bibliographic References

The standard way of typesetting bibliographic references used to be BibTeX. The original BibTeX, however, seems to be very outdated in various ways: it originally only supported 7 bit character sets and creating citation styles requires the usage of a kind of an archaic language. BibLaTeX resolves many of the drawbacks of BibTeX; when combined with the biber engine, it supports full UTF-8 unicode, therefore correct sorting of the references now works out of the box; also creating citation styles can now be done using simple LaTeX commands.

6.1.8 Use cleveref for Internal References

LaTeX provides an easy-to-use reference mechanism using the \label and \ref macros. However, this requires some manual effort and the text needs to specify whether a reference is to a figure, section, or table. We often see in drafts artefacts such as ‘we discuss our findings in 4’; but what is ‘4’ here? Is it a section? A table? A figure?

To avoid such confusion, use the cleveref package, which automatically infers the type of the reference (see its documentation on how this works). The cleveref package furthermore avoids an additional, common mistake: between the name of the element and its reference one needs to have a non-breaking space that is often forgotten. Instead people are using normal spaces that can break at the end of a line which looks very ugly.

Please note that, in contrast to most other packages, cleveref has to be loaded *after* the hyperref package!

6.2 Loading se2packages

When you load the se2packages package it will automatically load the csquotes and booktabs packages because we believe that you definitely should use them. Still, it is possible to avoid this by setting the following load-time options to the package.

csquotes	csquotes = $\langle true, false \rangle$
nocsquotes	nocsquotes

The argument to csquotes can be one of true or false. The latter does not load csquotes, the former is the default value. By using nocsquotes you can also avoid that csquote is loaded.

booktabs	booktabs = $\langle true, false \rangle$
nobooktabs	nobooktabs

The argument to booktabs can be one of true or false. The latter does not load booktabs, the former is the default value. By using nobooktabs you can also avoid that booktabs is loaded.

The siunitx package is helpful to set quantities and to automatically format numbers consistently. The following load-time option loads it automatically.

siunitx	siunitx = $\langle true, false \rangle$
---------	---

Decides whether the package loads siunitx and sets the options for siunitx to the values we recommend. The default value is false, set it to true to load siunitx.

We provide a load-time option to load minted and configure it.

minted	minted = $\langle true, false \rangle$
--------	--

Decides whether the package loads minted and sets the options for minted to the values we recommend. The default value is false, set it to true to load minted. Note that minted requires additional installation effort and the use of the -shell-escape option, see its documentation.

We also provide a load-time option to load listings and configure it. This option and the minted option are mutually exclusive!

`listings` `listings = $\langle true, false \rangle$`

Decides whether the package loads listings and sets the options for listings to the values we recommend. The default value is false, set it to true to load listings.

We provide a load-time option to load selnolig.

`selnolig` `selnolig = $\langle true, false \rangle$`
`noselnolig` `noselnolig`

The argument to selnolig can be one of true or false. The latter does not load selnolig, the former is the default value. By using noselnolig you can also avoid that selnolig is loaded.

We provide a load-time option to load lua-widow-control.

`widowcontrol` `widowcontrol = $\langle true, false \rangle$`
`nowidowcontrol` `nowidowcontrol`

The argument to widowcontrol can be one of true or false. The former loads lua-widow-control, the latter is the default value. By using nowidowcontrol you can also avoid that lua-widow-control is loaded.

We provide a load-time option to load and configure microtype.

`microtype` `microtype = $\langle true, false \rangle$`
`nomicrotype` `nomicrotype`

The argument to microtype can be one of true or false. The latter does not load microtype, the former is the default value. By using nomicrotype you can also avoid that microtype is loaded.

We provide a load-time option to load and configure biblatex.

`biblatex` `biblatex = $\langle true, false, alphabetic, numeric \rangle$`

Decides whether the package loads biblatex and sets the options for biblatex to the values we recommend. The default value is false, set it to true to load biblatex.

By setting the value to alphabetic, se2packages sets the citation style for biblatex to its alphabetic one; selecting numeric loads the numeric style as provided by the acmart bundle of the ACM. The value true also loads the latter style as a default.

Note that for the numeric style, we provide an enhanced `\autocite` command, which does not only print the citation mark in the text but also a short entry listing of the bibliography entry in the margin column of the page. This entry is only printed for the first occurrence of a citation per chapter to not clutter the margin column too much. The other citation commands from biblatex work as usual.

Additionally, we provide a load-time option to load cleveref. This option makes use of \LaTeX 's hook system to load it as the very last thing in the preamble. You shall not use this option, but load cleveref on your own, if your document requires packages that need to be loaded even *after* cleveref.

`cleveref` `cleveref = $\langle true, false \rangle$`

Decides whether the package load cleveref. The default value is false, set it to true to load cleveref.

Lastly, we provide one option to load all recommended packages (with minted preferred over listings).

`all` `all = \langle true, false \rangle`

Decides whether the package loads all recommended packages. The default value is false, set it to true to load them.

6.3 Additional Recommended Packages

The following packages are not part of `se2packages` because they serve a very specific purpose. They might not be needed by many thesis writers, however, we mention them here in order to give you a pointer. We list them in alphabetic order.

- `algorithm2e`: provides tooling for typesetting algorithm diagrams. We recommend loading it with the following options:

`\usepackage[ruled,noline,noend,linesnumbered]{algorithm2e}`

- `hvfloating`: a package to control captions, fullpage, and double-page floats. We recommend to load it and use its `\tabcaption` for table captions.
- `lettrine`: allows to start a paragraph with a large initial. This is a beautiful opener for the first paragraph of a thesis' main content.
- `mathtools`: an enhanced version of the famous $\mathcal{A}\mathcal{M}\mathcal{S}$ mathpackage that provides more functionality and fixes some of the known bugs.
- `pdfx`: adds support for PDF/X and PDF/A, which is useful for creating documents that can be archived, for example, by the University's library.
- `pgfplots`: a library for creating all kinds of plots, based on `pgf`, which is also the basis of the `tikz` package.
- `sidenotesplus`: a package to place all kinds of objects in the margin of a document, from footnotes (then called sidenotes) to figures and tables.
- `subcaption`: support for sub-captions and sub-figures.
- `tabularray`: a rewrite of \LaTeX 's array and tabular abilities in \LaTeX 3. While the package offers a great combination of several other packages' functionality, it tends to be quite slow for large tables due to the way it is implemented internally.
- `tcolorbox`: allows to typeset coloured boxes, for example, for short summaries on research questions or hypotheses.
- `tikz`: for creating all kinds of figures. Beware: TikZ is a really huge package with a lot of functionality and a manual of more than 1300 pages.

References

- [1] Dirk Beyer, Stefan Löwe, and Philipp Wendler: *Reliable benchmarking: requirements and solutions*. STTT 21(1): 1–29 (2019)
- [2] Donald E. Knuth: *The \TeX book*. Addison-Wesley (1986)

Part II

Implementation

The second part of this file provides the implementation of the package for a better understanding of what is happening.

1 Global helpers

These helpers might be useful for many exported packages and classes, thus we keep them on the global level of this implementation.

```

1 <*init>

   Load only the essential support (expl3) ‘up-front’, and only if required.
2 \ifundefined{ExplLoaderFileDate}
3   { \RequirePackage{expl3} }
4   {}

   Make sure that the version of l3kernel in use is sufficiently new. We use \ExplFileDate as
\ifpackageafter does not work for pre-loaded expl3 in the absence of the package.
5 \ifl@t@r\ExplLoaderFileDate{2020-01-09}
6   {}
7   {%
8     \PackageError{se2colors}{Support package expl3 too old}
9     {%
10      You need to update your installation of the bundles 'l3kernel' and
11      'l3packages'.\MessageBreak
12      Loading~se2colors~will~abort!%
13    }%
14    \endinput
15  }%
```

`\IfFormatAtLeastTF` This macro is not present in older kernels, thus we use the \LaTeX 2 ϵ mechanism as this is correct for this case.

```
16 \providecommand \IfFormatAtLeastTF { \ifl@t@r \fmtversion }
```

(End of definition for `\IfFormatAtLeastTF`. This function is documented on page 2.)

```
17 </init>
```

2 The se2thesis implementation

Start the DocStrip guards.

```
18 <*class>
```

Identify the internal prefix (\LaTeX 3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
19 <@@=slcd>
```

Identify the class and give the overall version number.

```
20 \ProvidesExplClass {se2thesis} {2026-04-03} {4.4.1}
21 {A thesis class for the Chair of Software Engineering II}
```

`\slcd_package_if_loaded:nTF` Defines various \LaTeX 3 variants for the internal `\@ifpackageloaded` macro to check whether a package has been loaded.

```

\slcd_package_if_loaded:nT
\slcd_package_if_loaded:nF
\slcd_package_if_loaded:nTF
\slcd_package_if_loaded:p:n
22 \prg_new_conditional:Nnn \slcd_package_if_loaded:n { p, T, F, TF }
23 {
24   \use:c { \@ifpackageloaded }
25   { #1 }
26   { \prg_return_true: }
27   { \prg_return_false: }
28 }
```

(End of definition for \slcd_package_if_loaded:nTF and others. These functions are documented on page 3.)

Load required packages early.

```

29 \RequirePackage{graphicx}
30 \RequirePackage{translations}
31 \LoadDictionary{se2translations}
32 \DeclareTranslationFallback{version-of-date}{%
33   Version~\l__slcd_version_tl\ of~\@date
34 }
35 \DeclareTranslation{German}{version-of-date}{%
36   Version~\l__slcd_version_tl\ vom~\@date
37 }
38 \DeclareTranslation{English}{version-of-date}{%
39   Version~\l__slcd_version_tl\ of~\@date
40 }

```

2.1 Define Variables

The following variables are necessary for the argument handling.

\l__slcd_paper_int A variable to store the key of the page size selected by the user.

```
41 \int_new:N \l__slcd_paper_int
```

(End of definition for \l__slcd_paper_int.)

We also need properties to store class options that are not for us, thus shall be handled by the underlying base class.

\l__slcd_base_class_tl Store the known and the unknown class options. The latter will be forwarded to the base class later.

```

\l__slcd_clsopts_prop
\l__slcd_unknown_clsopts_prop
42 \tl_new:N \l__slcd_base_class_tl
43 \prop_new:N \l__slcd_clsopts_prop
44 \prop_new:N \l__slcd_unknown_clsopts_prop

```

(End of definition for \l__slcd_base_class_tl, \l__slcd_clsopts_prop, and \l__slcd_unknown_clsopts_prop.)

Define internal variables to hold the values of the fields of the title page.

```

\l__slcd_version_tl
\l__slcd_degreeprogramme_tl
\l__slcd_matrnumber_tl
\l__slcd_supervisor_tl
\l__slcd_cosupervisor_tl
\l__slcd_advisor_tl
\l__slcd_coadvisor_tl
\l__slcd_department_tl
\l__slcd_institute_tl
\l__slcd_external_tl
\l__slcd_logofile_tl
\l__slcd_signature_tl
\l__slcd_location_tl
45 \tl_new:N \l__slcd_version_tl
46 \tl_new:N \l__slcd_degreeprogramme_tl
47 \tl_new:N \l__slcd_matrnumber_tl
48 \tl_new:N \l__slcd_supervisor_tl
49 \tl_new:N \l__slcd_cosupervisor_tl
50 \tl_new:N \l__slcd_advisor_tl
51 \tl_new:N \l__slcd_coadvisor_tl
52 \tl_new:N \l__slcd_department_tl
53 \tl_new:N \l__slcd_institute_tl
54 \tl_new:N \l__slcd_external_tl
55 \tl_new:N \l__slcd_logofile_tl
56 \tl_new:N \l__slcd_signature_tl
57 \tl_new:N \l__slcd_location_tl

```

(End of definition for \l__slcd_version_tl and others.)

Define several dimensions for the typearea package to define the package style.

```

\l__slcd_marginspace_dim
\l__slcd_headmarkspace_dim
\l__slcd_rulespace_dim
\l__slcd_pagemark_minipage_dim
\l__slcd_ruleraise_dim
\l__slcd_rulewidth_dim
\l__slcd_rulethickness_dim

58 \dim_new:N \l__slcd_marginspace_dim
59 \dim_new:N \l__slcd_headmarkspace_dim
60 \dim_new:N \l__slcd_rulespace_dim
61 \dim_new:N \l__slcd_pagemark_minipage_dim
62 \dim_new:N \l__slcd_ruleraise_dim
63 \dim_new:N \l__slcd_rulewidth_dim
64 \dim_new:N \l__slcd_rulethickness_dim
65 \dim_gset:Nn \l__slcd_marginspace_dim { -1.85cm }
66 \dim_gset:Nn \l__slcd_headmarkspace_dim { 0.75cm }
67 \dim_gset:Nn \l__slcd_rulespace_dim { 10pt }
68 \dim_gset:Nn \l__slcd_pagemark_minipage_dim { 1.5cm }
69 \dim_gset:Nn \l__slcd_ruleraise_dim { -5pt }
70 \dim_gset:Nn \l__slcd_rulewidth_dim { 1.25pt }
71 \dim_gset:Nn \l__slcd_rulethickness_dim { 15pt }

```

(End of definition for `\l__slcd_marginspace_dim` and others.)

2.2 Load-time options

We define the key-value interface for the class.

```

\l__slcd_base_class_tl
\l_slcd_unknown_clsopts_prop
\l__slcd_paper_int
\l__slcd_thesis_type_tl
\l__slcd_licensetype_tl
\l__slcd_licensemodifier_tl
\l__slcd_licenseversion_tl
\l__slcd_colormode_tl

72 \keys_define:nn { seiithesis }
73 {
74   class .choice:,
75   class / report .meta:n = {class=scrreprt},
76   class / scrreprt .code:n = \tl_gset:Nn \l__slcd_base_class_tl {scrreprt},
77   class / book .meta:n = {class=scrbook},
78   class / scrbook .code:n = \tl_gset:Nn \l__slcd_base_class_tl {scrbook},
79   class .initial:n = scrbook,
80
81   paper .choices:nn = {a4,b5}{
82     \int_gset_eq:NN \l__slcd_paper_int \l_keys_choice_int
83   },
84   paper .initial:n = a4,
85
86   logfile .tl_gset:N = \l__slcd_logofile_tl,
87   logfile .initial:n =,
88
89   thesistype .choice:,
90   thesistype / bachelor .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {bachelor},
91   thesistype / bachelorproposal .code:n = {
92     \tl_gset:Nn \l__slcd_thesis_type_tl {bachelorproposal}
93   },
94   thesistype / master .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {master},
95   thesistype / masterproposal .code:n = {
96     \tl_gset:Nn \l__slcd_thesis_type_tl {masterproposal}
97   },
98   thesistype / phd .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {phd},
99   thesistype / phdeng .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {phdeng},
100  thesistype / phdphil .code:n = \tl_gset:Nn \l__slcd_thesis_type_tl {phdphil},
101  thesistype / phdproposal .code:n = {
102    \tl_gset:Nn \l__slcd_thesis_type_tl {phdproposal}

```

```

103 },
104 thesistype .initial:n = master,
105
106 colormode .choices:nn = {4C,CMYK,cmyk,RGB,rgb,BW,bw,gray}{
107   \tl_gset_eq:NN \l__slcd_colormode_tl \l_keys_choice_tl
108 },
109 colormode .initial:n = cmyk,
110
111 unknown .code:n = {
112   \prop_gput:NvN \l__slcd_unknown_clsopts_prop \l_keys_key_str {#1}
113 },
114 }

```

(End of definition for \l__slcd_base_class_tl and others.)

Handle the options

```

115 \IfFormatAtLeastTF { 2022-06-01 }
116 { \ProcessKeyOptions [ seiithesis ] }
117 {
118   \RequirePackage{ l3keys2e }
119   \ProcessKeysOptions { seiithesis }
120 }

```

Handle the known options for base class

```

121 \prop_map_inline:Nn \l__slcd_clsopts_prop
122 {
123   \tl_if_empty:nTF {#2}
124   { \PassOptionsToClass {#1} {\l__slcd_base_class_tl} }
125   {
126     \clist_map_inline:nn {#2}
127     { \PassOptionsToClass {#1=#1} {\l__slcd_base_class_tl} }
128   }
129 }

```

Load the base class

```

130 \LoadClass{\l__slcd_base_class_tl}

```

Attempt to handle the unknown options

```

131 \prop_map_inline:Nn \l__slcd_unknown_clsopts_prop
132 {
133   \cs_if_exist:cT {KV@KOMAs.\l__slcd_base_class_tl.cls@#1}
134   {
135     \tl_if_empty:nTF {#2}
136     { \KOMAOptions{#1} }
137     { \KOMAOption{#1}{#2}}
138   }
139 }

```

2.3 Package loading

We load some packages with options that depend on options to the se2thesis class. Thus, we load them here to be able to hand them over the respective values.

We start with the se2colors and se2fonts packages.

```

140 \PassOptionsToPackage{\l__slcd_colormode_tl}{se2colors}
141 \RequirePackage{se2colors}
142

```

```
143 \RequirePackage{se2fonts}
```

2.4 User macros for the title page

In addition to the macros provided by the KOMA-Script classes for the title-page values (e.g. `\author`, `\title`), provide these additional macros to the user.

`\version` Specify the version of the document, e.g., a git hash.

```
144 \ProvideDocumentCommand \version { m }
145 {
146   \tl_set:Nn \l__slcd_version_tl {#1}
147 }
```

(End of definition for `\version`. This function is documented on page 4.)

`\degreeprogramme` Specify the degree programme the thesis is meant to be accepted in.

```
148 \ProvideDocumentCommand \degreeprogramme { m }
149 {
150   \tl_set:Nn \l__slcd_degreeprogramme_tl {#1}
151 }
```

(End of definition for `\degreeprogramme`. This function is documented on page 4.)

`\matrnumber` Specify the matriculation number of the student.

```
152 \ProvideDocumentCommand \matrnumber { m }
153 {
154   \tl_set:Nn \l__slcd_matrnumber_tl {#1}
155 }
```

(End of definition for `\matrnumber`. This function is documented on page 4.)

`\supervisor` Specify the supervisor and co-supervisor of the thesis, usually a professor.
`\cosupervisor`

```
156 \ProvideDocumentCommand \supervisor { m }
157 {
158   \tl_set:Nn \l__slcd_supervisor_tl {#1}
159 }
160 \ProvideDocumentCommand \cosupervisor { m }
161 {
162   \tl_set:Nn \l__slcd_cosupervisor_tl {#1}
163 }
```

(End of definition for `\supervisor` and `\cosupervisor`. These functions are documented on page 4.)

`\advisor` Specify the advisor and co-advisor of the thesis, usually a PhD student or postdoc.
`\coadvisor`

```
164 \ProvideDocumentCommand \advisor { m }
165 {
166   \tl_set:Nn \l__slcd_advisor_tl {#1}
167 }
168 \ProvideDocumentCommand \coadvisor { m }
169 {
170   \tl_set:Nn \l__slcd_coadvisor_tl {#1}
171 }
```

(End of definition for `\advisor` and `\coadvisor`. These functions are documented on page 4.)

`\department` Specify the university's department and institute you are writing the thesis for.

```
\institute
172 \ProvideDocumentCommand \department { m }
173 {
174   \tl_set:Nn \l__slcd_department_tl {#1}
175 }
176 \ProvideDocumentCommand \institute { o m }
177 {
178   \tl_set:Nn \l__slcd_institute_tl {#2}
179 }
```

(End of definition for `\department` and `\institute`. These functions are documented on page 4.)

`\external` Specify an external referee.

```
180 \ProvideDocumentCommand \external { m }
181 {
182   \tl_set:Nn \l__slcd_external_tl {#1}
183 }
```

(End of definition for `\external`. This function is documented on page 4.)

`\location` Specify the location for the signature field.

```
184 \ProvideDocumentCommand \location { m }
185 {
186   \tl_set:Nn \l__slcd_location_tl {#1}
187 }
```

(End of definition for `\location`. This function is documented on page 5.)

2.5 Define logo, paper size, and paper style

For the logo on the titlepage, we define further variables to store its height and a box to store the logo itself.

```
\l__slcd_logo_height_dim
\l__slcd_logo_box
188 \dim_if_exist:NF \l__slcd_logo_height_dim
189 {
190   \dim_new:N \l__slcd_logo_height_dim
191   \int_compare:nTF { \l__slcd_paper_int=1 }
192   {
193     \dim_gset:Nn \l__slcd_logo_height_dim { 67.5pt }
194   } {
195     \dim_gset:Nn \l__slcd_logo_height_dim { 56.8pt }
196   }
197 }
198 \box_if_exist:NF \l__slcd_logo_box
199 {
200   \box_new:N \l__slcd_logo_box
201 }
202 \tl_if_empty:NF \l__slcd_logofile_tl
203 {
204   \hbox_gset:Nn \l__slcd_logo_box
205   {
206     \includegraphics[%
207       height=\l__slcd_logo_height_dim%
```

```

208     ]{\l__slcd_logofile_tl}
209   }
210 }

```

(End of definition for \l__slcd_logo_height_dim and \l__slcd_logo_box.)

Set the paper size depending on the selected paper option.

```

211 \int_compare:nTF { \l__slcd_paper_int=1 }
212 {
213   \areaset[current]{350pt}{567pt}
214   \setlength{\marginparsep}{8.5cm}
215   \setlength{\marginparsep}{1.5em}
216 }{
217   \areaset[current]{350pt}{567pt}
218   \setlength{\marginparsep}{7.4cm}
219   \setlength{\marginparsep}{1.5em}
220 }

```

Provide the package style. We start by loading the scrlayer-scrpage package with the appropriate options and set some basic properties.

```

221 \PassOptionsToPackage{automark}{scrlayer-scrpage}
222 \RequirePackage{scrlayer-scrpage}
223 \clearpairofpagestyles
224 \setkomafont{pagefoot}{\normalfont\sffamily}

```

We can then define the footer for odd pages, which will appear on the right side of the page's footer. This definition contains first, as an optional argument, the style of a page with pagestyle set to empty, i.e., a page where a new chapter starts, and afterwards the style of a regular right-hand side page.

```

225 \rofoot[ {%
226   \group_begin: \ \group_end:
227   \footnotesize%
228   \hspace*{\l__slcd_headmarkspace_dim}%
229   \group_begin:
230     \color{UPSE2-Blue}%
231     \rule{\l__slcd_ruleraise_dim}{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
232   \group_end:
233   \hspace*{\l__slcd_rulespace_dim}%
234   \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
235     \normalsize\textbf{\pagemark}%
236   \end{minipage}%
237   \hspace{\l__slcd_marginspace_dim}%
238 ]]{%
239   \group_begin: \ \group_end:
240   \footnotesize%
241   \group_begin:
242     \color{UPSE2-Blue}\headmark
243   \group_end:
244   \hspace*{\l__slcd_rulespace_dim}%
245   \group_begin:
246     \color{UPSE2-Blue}%
247     \rule{\l__slcd_ruleraise_dim}{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
248   \group_end:
249   \hspace*{\l__slcd_rulespace_dim}%
250   \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
251     \normalsize\textbf{\pagemark}%

```

```

252 \end{minipage}%
253 \hspace{\l__slcd_marginspace_dim}%
254 }

```

Similarly, we define the footer for even pages, which will appear on the left side of the page's footer.

```

255 \lefoot[{\%
256 \null\hspace{\l__slcd_marginspace_dim}%
257 \footnotesize%
258 \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
259 \raggedleft\normalsize\textbf{\pagemark}%
260 \end{minipage}%
261 \footnotesize%
262 \hspace*{\l__slcd_rulespace_dim}%
263 \group_begin:
264 \color{UPSE2-Blue}%
265 \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
266 \group_end:
267 }]{\%
268 \null\hspace{\l__slcd_marginspace_dim}%
269 \footnotesize%
270 \begin{minipage}[b]{\l__slcd_pagemark_minipage_dim}%
271 \raggedleft\normalsize\textbf{\pagemark}%
272 \end{minipage}%
273 \footnotesize%
274 \hspace*{\l__slcd_rulespace_dim}%
275 \group_begin:
276 \color{UPSE2-Blue}%
277 \rule[\l__slcd_ruleraise_dim]{\l__slcd_rulewidth_dim}{\l__slcd_rulethickness_dim}%
278 \group_end:
279 \hspace*{\l__slcd_headmarkspace_dim}%
280 \group_begin:
281 \color{UPSE2-Blue}\headmark
282 \group_end:
283 }

```

Finally, set the page style.

```

284 \pagestyle{scrheadings}

```

2.6 The title page

We start out by adjusting some KOMA-Script fonts.

```

285 \setkomafont{title}{\Huge}
286 \setkomafont{subtitle}{\Large}
287 \setkomafont{subject}{\normalsize}
288 \setkomafont{author}{\large}
289 \setkomafont{date}{\normalsize}
290 \setkomafont{publishers}{\normalsize}

```

`\author` Allow for automated splitting of author's names.
`\@author`

```

291 \seq_new:N \l__slcd_author_seq
292 \renewcommand*\author[2][{}{
293 \seq_gset_split:Nnn \l__slcd_author_seq {\and} {#2}
294 \tl_if_empty:nTF {#1}

```

```

295 { \tl_set:Nn \l__slcd_signature_tl {#2} }
296 { \tl_set:Nn \l__slcd_signature_tl {#1} }
297 }
298 \renewcommand*{\@author}{
299   \group_begin:
300   \seq_use:Nnnn \l__slcd_author_seq {\GetTranslation{and}} {,} {\&}
301   \group_end:
302 }

```

(End of definition for \@author and \@author. These functions are documented on page 5.)

Define a new layer using the functionality from scrlayer-scrpage for the logo image.

```

303 \DeclareNewLayer[
304   mode=picture,
305   foreground,
306   hoffset=\paperwidth-\coverpagerightmargin-\box_wd:N \l__slcd_logo_box,
307   voffset=\coverpagetopmargin+1.5in+\ht\strutbox,
308   width=\box_wd:N \l__slcd_logo_box,
309   height=\box_ht:N \l__slcd_logo_box,
310   contents={\putUL{\box_use:N \l__slcd_logo_box}},
311 ]{title.seii.logo}
312 \DeclareNewPageStyleByLayers{title.seii}{title.seii.logo}
313 \renewcommand*{\titlepagestyle}{title.seii}

```

Redefine the \maketitle command. The following code is an adapted version of the corresponding KOMA-Script macro by Markus Kohm.

```

314 \renewcommand*{\maketitle}[1][1]{
315   \begin{titlepage}
316     \setcounter{page}{#1}
317     \def\thefootnote{\fnsymbol{footnote}}
318     \edef\titlepage@restore{%
319       \noexpand\endgroup
320       \noexpand\global\noexpand\@colht\the\@colht
321       \noexpand\global\noexpand\@colroom\the\@colroom
322       \noexpand\global\vsizethe\vsizethe
323       \noexpand\global\noexpand\@titlepageiscoverpagefalse
324       \noexpand\let\noexpand\titlepage@restore\noexpand\relax
325     }%
326     \begingroup
327     \topmargin=\dimexpr \coverpagetopmargin-1in\relax
328     \oddsidemargin=\dimexpr 0in\relax
329     \evensidemargin=\dimexpr 0in\relax
330     \textwidth=\dimexpr \paperwidth-2in\relax
331     \textheight=\dimexpr
332     \paperheight-\coverpagetopmargin-\coverpagebottommargin\relax
333     \headheight=0pt
334     \headsep=0pt
335     \footskip=\baselineskip
336     \@colht=\textheight
337     \@colroom=\textheight
338     \vsizethe=\textheight
339     \columnwidth=\textwidth
340     \hsize=\textwidth
341     \linewidth=\hsize
342     \setparsizes{\z@}{\z@}{\z@}{\plus 1fil}\par@update relative

```

```

343 \thispagestyle{title.seii}
344 %
345 \@maketitle
346 %
347 \if@twoside
348   \@tempwattrue
349   \if@tempswa
350     \next@tpage
351     \begin{minipage}[t]{\textwidth}
352       \uppertitleback
353     \end{minipage}
354     \vfill
355     \begin{minipage}[b]{\textwidth}
356       \lowertitleback
357     \end{minipage}\par
358     \thanks\let\thanks\empty
359   \fi
360 \fi
361 \ifx\tITLEPAGE@restore\relax\else\clearpage\tITLEPAGE@restore\fi
362 \end{titlepage}
363 }

```

`\l__slcd_title_box` Define a box for the title if it does not yet exist.

```

364 \box_if_exist:NF \l__slcd_title_box
365 {
366   \box_new:N \l__slcd_title_box
367 }

```

(End of definition for \l__slcd_title_box.)

`\@maketitle` Redecclare the `\@maketitle` macro.

```

368 \renewcommand*{\@maketitle}{%
369   \group_begin:
370     \setparsizes{\z@}{\z@}{\z@\@plus 1fil}\par@updaterelative
371     \thispagestyle{title.seii}
372     \hbox_gset:Nn \l__slcd_title_box
373     {
374       \parbox{\textwidth}{\__slcd_print_title:}
375     }
376     \null
377     \skip_vertical:n { 2.5 \box_ht:N \l__slcd_logo_box }
378     \box_use:N \l__slcd_title_box
379     \skip_vertical:n { .5 \box_ht:N \l__slcd_logo_box }
380   \group_end:
381   \thanks\let\thanks\empty
382 }

```

(End of definition for \@maketitle. This function is documented on page 4.)

Load the ifthen package.

```

383 \RequirePackage{ifthen}

```

Prints the title formatted appropriately. We start with printing the title, optional subtitle, and the author names.

```

384 \tl_new:N \g__slcd_title_tl

```

```

385 \cs_new:Nn \__slcd_print_title:
386 {
387   \group_begin:
388     \usekomafont{title}\centering\@title\par
389   \group_end:
390   \ifx\@subtitle\@empty\else{%
391     \medskip\usekomafont{subtitle}\centering\@subtitle\par%
392   }\fi
393   \bigskip
394   \group_begin:
395     \usekomafont{author}\centering\@author\par
396   \group_end:
397   \bigskip

```

The next block generates the text that describes the thesis. In case of a PhD thesis, this text is predefined to match the requirements. In case of a bachelor's or master's thesis, or a proposal thereof, we generate a text based on the values of the `thesistype` load-time option and the values of the `\degreeprogramme`, `\department`, and `\institute` variables.

```

398 \tl_set:Nn
399   \g__slcd_title_tl
400   {
401     \begin{center}
402       \tl_if_eq:NnTF \l__slcd_thesis_type_tl { phd }
403       {
404         Dissertation~ zur~ Erlangung~ des~ Doktorgrades\\
405         der~ Naturwissenschaften~ (Dr.\,rer.\,nat.)\\
406         eingereicht~ an~ der~ Fakultät~ für~ Informatik~ und~ Mathematik\\
407         der~ Universität~ Passau\\
408         \rule{\textwidth}{.1pt}\\
409         Dissertation~ submitted~ to\\
410         the~ Faculty~ of~ Computer~ Science~ and~ Mathematics\\
411         of~ the~ University~ of~ Passau\\
412         in~ partial~ fulfillment~ of~ obtaining\\
413         the~ degree~ of~ a~ Doctor~ of~ Natural~ Sciences
414       } {
415         \tl_if_eq:NnTF \l__slcd_thesis_type_tl { phdeng }
416         {
417           Dissertation~ zur~ Erlangung~ des~ Doktorgrades\\
418           der~ Ingenieurwissenschaften~ (Dr.-Ing.)\\
419           eingereicht~ an~ der~ Fakultät~ für~ Informatik~ und~ Mathematik\\
420           der~ Universität~ Passau\\
421           \rule{\textwidth}{.1pt}\\
422           Dissertation~ submitted~ to\\
423           the~ Faculty~ of~ Computer~ Science~ and~ Mathematics\\
424           of~ the~ University~ of~ Passau\\
425           in~ partial~ fulfillment~ of~ obtaining\\
426           the~ degree~ of~ a~ Doctor~ of~ Engineering
427         } {
428           \tl_if_eq:NnTF \l__slcd_thesis_type_tl { phdphil }
429           {
430             Dissertation~ zur~ Erlangung~ des~ Doktorgrades\\
431             der~ Naturphilosophie~ (Dr.\,phil.\,nat.)\\
432             eingereicht~ an~ der~ Fakultät~ für~ Informatik~ und~ Mathematik\\
433             der~ Universität~ Passau\\

```

```

434 \rule{\textwidth}{.1pt}\\
435 Dissertation~ submitted~ to\\
436 the~ Faculty~ of~ Computer~ Science~ and~ Mathematics\\
437 of~ the~ University~ of~ Passau\\
438 in~ partial~ fulfillment~ of~ obtaining\\
439 the~ degree~ of~ a~ Doctor~ of~ Natural~ Philosophy
440 } {
441 \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelor }
442 { \GetTranslation{Bachelor-thesis} }
443 \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelorproposal }
444 { \GetTranslation{Bachelor-thesis-proposal} }
445 \tl_if_eq:NnT \l__slcd_thesis_type_tl { master }
446 { \GetTranslation{Master-thesis} }
447 \tl_if_eq:NnT \l__slcd_thesis_type_tl { masterproposal }
448 { \GetTranslation{Master-thesis-proposal} }
449 \tl_if_eq:NnT \l__slcd_thesis_type_tl { phdproposal }
450 { \GetTranslation{PhD-thesis-proposal} }
451 \tl_if_empty:NF \l__slcd_degreeprogramme_tl
452 {
453 \ in~\l__slcd_degreeprogramme_tl
454 }
455 \par
456 \tl_if_empty:NF \l__slcd_department_tl { \l__slcd_department_tl \par }
457 \tl_if_empty:NF \l__slcd_institute_tl { \l__slcd_institute_tl \par }
458 }
459 }
460 }
461 \end{center}\par\bigskip

```

Finally, generate a table with information about supervisors, advisors, etc.

```

462 \begin{center}
463 \begin{tabular}{@{} l @{\quad} l}
464 \tl_if_empty:NF \l__slcd_matrnumber_tl
465 {
466 \GetTranslation{Matrnumber} & \l__slcd_matrnumber_tl \\
467 }
468 \tl_if_empty:NF \l__slcd_supervisor_tl
469 {
470 \GetTranslation{Supervisor} & \l__slcd_supervisor_tl \\
471 }
472 \tl_if_empty:NF \l__slcd_cosupervisor_tl
473 {
474 \GetTranslation{Co-supervisor} & \l__slcd_cosupervisor_tl \\
475 }
476 \tl_if_empty:NF \l__slcd_advisor_tl
477 {
478 \GetTranslation{Advisor} & \l__slcd_advisor_tl \\
479 }
480 \tl_if_empty:NF \l__slcd_coadvisor_tl
481 {
482 \GetTranslation{Co-advisor} & \l__slcd_coadvisor_tl \\
483 }
484 \tl_if_empty:NF \l__slcd_external_tl
485 {
486 \GetTranslation{External} & \l__slcd_external_tl \\

```

```

487         }
488     \end{tabular}
489 \end{center}
490 \par\medskip

```

Last, print the date or the version.

```

491     \group_begin:
492     \usekomafont{date}
493     \centering
494     \tl_if_empty:NTF \l__slcd_version_tl
495     { \@date }
496     { \GetTranslation{version-of-date} }
497     \par\smallskip
498     \group_end:
499 }
500 \exp_args:NNV
501 \tl_use:N
502 \g__slcd_title_tl
503 }

```

`\@lowertitleback` Afterwards, override the definition of `\@lowertitleback`. To prevent line breaks in the title (that might be necessary to layout it properly on the front title page), we place a group around `\@title` and temporarily redefine `\` to do nothing.

```

504 \renewcommand*{\@lowertitleback}{%
505     \group_begin:
506     \noindent\textbf{\@author}:\
507     \group_begin:
508     \let\relax\relax
509     \emph{\@title}
510     \group_end:\
511     \tl_if_eq:NnT \l__slcd_thesis_type_tl { bachelor }
512     { \GetTranslation{Bachelor-thesis},~ }
513     \tl_if_eq:NnT \l__slcd_thesis_type_tl { master }
514     { \GetTranslation{Master-thesis},~ }
515     \tl_if_eq:NnT \l__slcd_thesis_type_tl { phd }
516     { \GetTranslation{PhD-thesis},~ }
517     \GetTranslation{up},~\the\year.
518     \group_end:
519 }

```

(End of definition for `\@lowertitleback`. This function is documented on page 5.)

2.7 Styling of the sectioning commans

We change the formatting of the chapter, section, and sub-section headings.

```

520 \addtokomafont{chapterprefix}{\raggedleft\bfseries}
521 \addtokomafont{chapter}{\mdseries}
522 \addtokomafont{section}{\large\mdseries}
523 \addtokomafont{subsection}{\normalsize\mdseries}
524 \renewcommand*{\chapterformat}{%
525     \enskip\mbox{%
526         \scalebox{3}{\color{UPSE2-DarkGray}\thechapter\autodot}%
527     }%
528 }

```



```

529 \renewcommand{\chapterlinesformat}[3]{%
530   \parbox[b]{\textwidth}{\hrulefill#2}\par%
531   #3\par\bigskip%
532   \hrule%
533 }
534 \RedeclareSectionCommand[afterskip=1.5\baselineskip]{chapter}
535 \renewcommand*{\chapterlineswithprefixformat}[3]{%
536   \Ifstr{#1}{chapter}
537     {#2\textls*[75]{\MakeUppercase{#3}}}% change definition for chapter
538     {#2#3}% original definition
539 }%
540 \renewcommand*{\sectionlinesformat}[4]{%
541   #3\textls*[75]{\MakeUppercase{#4}}%
542 }

    Change the loop of a \paragraph to be italic and end with a full stop.
543 \setkomafont{paragraph}{\normalsize\normalfont\itshape}
544 \AddToDoHook{heading/endgroup/paragraph}{\headingdot}
545 \newcommand*{\headingdot}[1]{.}

    Change the width of a dictum
546 \renewcommand*{\dictumwidth}{0.42\linewidth}

```

2.8 Provide an environment for abstracts

We want to allow abstracts in German and English, which is also a requirement when writing a thesis in English. First, ensure that the `\abstract` macro is available for all classes.

`\abstract`

```

547 \providecommand{\abstract}{}

```

(End of definition for \abstract. This function is documented on page 5.)

Then redefine the `abstract` environment such that it provides an optional argument for language selection.

abstract (env.) Used to typeset an abstract for the thesis. The optional argument allows to specify a language. As a default the current document language will be used.

```

548 \RenewDocumentEnvironment { abstract } { o }
549 {
550   \group_begin:
551     \IfNoValueF {#1} { \selectlanguage{#1} }
552     \scr@ifundefinedorrelax{chapter}{
553       \Iftocfeature{toc}{leveldown}
554       {\subsection*}
555       {\section*}
556     }{
557       \let\clearpage\relax
558       \Iftocfeature{toc}{leveldown}
559       {\section*}
560       {\chapter*}
561     } { \GetTranslation{Abstract} }
562   } {
563     \group_end:
564   }

```

2.9 Provide an environment for acknowledgements

Often, especially in a PhD thesis, one wants to acknowledge the help of certain people, for example, supervisors, family, and friends.

acknowledgements (*env.*) Use to typeset the acknowledgements for the thesis.

```
565 \NewDocumentEnvironment { acknowledgements } { o }
566 {
567   \group_begin:
568   \IfNoValueF {#1} { \selectlanguage{#1} }
569   \scr@ifundefinedorrelax{chapter}{
570     \Iftocfeature{toc}{leveldown}
571     {\subsection*}
572     {\section*}
573   }{
574     \Iftocfeature{toc}{leveldown}
575     {\section*}
576     {\chapter*}
577   } { \GetTranslation{Acknowledgements} }
578 } {
579   \group_end:
580 }
```

2.10 Document structuring macros

Ensure that these macros are defined. These are the exact definitions from KOMA-Script.

```
581 \newif\if@mainmatter\@mainmattertrue
```

`\frontmatter` Starts the frontmatter. Most notably, set the page numbers to roman.

```
582 \providecommand*\frontmatter{
583   {
584     \if@twoside\cleardoubleoddpagel\else\clearpage\fi
585     \@mainmatterfalse
586     \pagenumbering { roman }
587   }
```

(End of definition for \frontmatter. This function is documented on page 6.)

`\mainmatter` Starts the mainmatter or the backmatter. Most notably, set the page numbers to arabic.

```
\backmatter
588 \providecommand*\mainmatter{
589   {
590     \if@twoside\cleardoubleoddpagel\else\clearpage\fi
591     \@mainmattertrue
592     \pagenumbering { arabic }
593   }
594 \providecommand*\backmatter{
595   {
596     \if@twoside\cleardoubleoddpagel\else\clearpage\fi
597     \@mainmatterfalse
598   }
```

(End of definition for \mainmatter and \backmatter. These functions are documented on page 6.)

2.11 Declaration of authorship

`\authorshipDeclaration` Provide a command to typeset the authorship declaration.

```

599 \NewDocumentCommand \authorshipDeclaration { o }
600 {
601   \par
602   \group_begin:
603     \selectlanguage{ngerman}
604     \IfNoValueF {#1}
605       { \tl_gset:Nn \l__slcd_location_tl {#1} }
606
607     \tl_if_empty:NT \l__slcd_location_tl
608       {
609         \msg_new:nnn { seiithesis }
610           { no-location-specified }
611         {
612           You~ need~ to~ specify~ a~ location~ for~ the~ authorship~
613             declaration.~ Either~ via~ the~ location~ macro~ or~ via~ the~
614             optional~ argument~ of~ the~ authorshipDeclaration~ macro.
615         }
616         \msg_warning:nn { seiithesis } { no-location-specified }
617       }
618
619     \scr@ifundefinedorrelax{chapter}{
620       \Iftocfeature{toc}{leveldown}
621         {\subsection*}
622         {\section*}
623     }{
624       \Iftocfeature{toc}{leveldown}
625         {\section*}
626         {\chapter*}
627     } { Eigenständigkeitserklärung }
628
629     Hiermit~ versichere~ ich,~ \l__slcd_signature_tl,
630     \begin{enumerate}
631       \item dass~ ich~ die~ vorliegende~ Arbeit~ selbstständig~ und~ ohne~
632         unzulässige~ Hilfe~ verfasst~ und~ keine~ anderen~ als~ die~
633         angegebenen~ Quellen~ und~ Hilfsmittel~ benutzt,~ sowie~ die~
634         wörtlich~ und~ sinngemäß~ übernommenen~ Passagen~ aus~ anderen~
635         Werken~ kenntlich~ gemacht~ habe.
636       \item Außerdem~ erkläre~ ich,~ dass~ ich~ der~ Universität~ ein~
637         einfaches~ Nutzungsrecht~ zum~ Zwecke~ der~ Überprüfung~ mittels~
638         einer~ Plagiatsoftware~ in~ anonymisierter~ Form~ einräume.
639     \end{enumerate}\par
640     \bigskip
641     \noindent \l__slcd_location_tl,~ \@date\hfill
642     \signatureBox{\l__slcd_signature_tl}
643   \group_end:
644   \\\strut\cleardoublepage
645 }
```

(End of definition for \authorshipDeclaration. This function is documented on page 6.)

`\signatureBox` Provide a box for the signature.

```

646 \newcommand*{\signatureBox}[2][5cm]{
647   \parbox[t]{#1}{
648     \centering
649     \rule{\linewidth}{.3pt}\makebox[0pt][c]{#2}
650   }
651 }

```

(End of definition for `\signatureBox`. This function is documented on page 6.)

2.12 Research questions and summary boxes

We utilise the `ntheorem` package for defining new theorem environments that are used for defining research questions and hypotheses. Therefore, start with loading this package. `ntheorem`.

```

652 \slcd_package_if_loaded:nT { amsmath }
653 {
654   \PassOptionsToPackage{amsmath}{ntheorem}
655 }
656 \RequirePackage{ntheorem}
657 \theoremseparator{:}

```

`resq (env.)` We can then define the `resq` and `hyp` environments using the `\newtheorem` macro from `ntheorem`.

```

658 \newtheorem{resq}{Research~ Question}
659 \newtheorem{hyp}{Hypothesis}

```

For the summary boxes, we utilise the `tcolorbox` package. We start with loading this package.

```

660 \RequirePackage{tcolorbox}

```

`summary (env.)` The summary environment expects a label and has the summary text in its content.

```

661 \ExplSyntaxOff
662 \NewDocumentEnvironment { summary } { m +b }
663 {%
664   \begin{tcolorbox}[%
665     size=fbox,%
666     rounded corners=all,%
667     attach title to upper,%
668     coltitle=black,%
669     fonttitle=\bfseries,%
670     title={Summary #1},
671     after title={:~\ },
672   ]
673     #2
674   } {%
675     \end{tcolorbox}%
676   }
677 \ExplSyntaxOn

```

`\summarybox` The `summarybox` macro simplifies the usage of the `summary` environment.

```

678 \NewDocumentCommand { \summarybox } { m m }
679 {
680   \begin{summary}{#1} #2 \end{summary}
681 }

```

(End of definition for \summarybox. This function is documented on page ??.)

682 \langle /class \rangle

3 Translations for se2thesis

683 \langle *translations \rangle

3.1 English Translations

684 \langle *english \rangle

We provide the following English translations.

685 \ProvideDictionaryFor{English}{se2translations}[2026/04/03]
686 \ProvideDictTranslation{abstract}{abstract}
687 \ProvideDictTranslation{Abstract}{Abstract}
688 \ProvideDictTranslation{acknowledgement}{acknowledgement}
689 \ProvideDictTranslation{Acknowledgement}{Acknowledgement}
690 \ProvideDictTranslation{acknowledgements}{acknowledgements}
691 \ProvideDictTranslation{Acknowledgements}{Acknowledgements}
692 \ProvideDictTranslation{advisor}{advisor}
693 \ProvideDictTranslation{Advisor}{Advisor}
694 \ProvideDictTranslation{advisors}{advisors}
695 \ProvideDictTranslation{Advisors}{Advisors}
696 \ProvideDictTranslation{co-advisor}{co-advisor}
697 \ProvideDictTranslation{Co-advisor}{Co-advisor}
698 \ProvideDictTranslation{co-advisors}{co-advisors}
699 \ProvideDictTranslation{Co-advisors}{Co-advisors}
700 \ProvideDictTranslation{matrnumber}{matriculation number}
701 \ProvideDictTranslation{Matrnumber}{Matriculation number}
702 \ProvideDictTranslation{supervisor}{supervisor}
703 \ProvideDictTranslation{Supervisor}{Supervisor}
704 \ProvideDictTranslation{co-supervisor}{co-supervisor}
705 \ProvideDictTranslation{Co-supervisor}{Co-supervisor}
706 \ProvideDictTranslation{external}{external examiner}
707 \ProvideDictTranslation{External}{External Examiner}
708 \ProvideDictTranslation{degreeprogramme}{programme}
709 \ProvideDictTranslation{Degreeprogramme}{Programme}
710 \ProvideDictTranslation{Bachelor-thesis}{Bachelor's Thesis}
711 \ProvideDictTranslation{Bachelor-thesis-proposal}{Bachelor's Thesis Proposal}
712 \ProvideDictTranslation{Master-thesis}{Master's Thesis}
713 \ProvideDictTranslation{Master-thesis-proposal}{Master's Thesis Proposal}
714 \ProvideDictTranslation{PhD-thesis}{PhD Thesis}
715 \ProvideDictTranslation{PhD-thesis-proposal}{PhD Thesis Proposal}
716 \ProvideDictTranslation{date}{date}
717 \ProvideDictTranslation{Date}{Date}
718 \ProvideDictTranslation{university-of-passau}{University of Passau}
719 \ProvideDictTranslation{up}{University of Passau}
720 \ProvideDictTranslation{fim}{Faculty of Computer Science and Mathematics}
721 \langle /english \rangle

3.2 German Translations

722 \langle *german \rangle

We provide the following German translations.

723 \ProvideDictionaryFor{German}{se2translations}[2026/04/03]
724 \ProvideDictTranslation{abstract}{Zusammenfassung}
725 \ProvideDictTranslation{Abstract}{Zusammenfassung}
726 \ProvideDictTranslation{acknowledgement}{Danksagung}
727 \ProvideDictTranslation{Acknowledgement}{Danksagung}
728 \ProvideDictTranslation{acknowledgements}{Danksagungen}
729 \ProvideDictTranslation{Acknowledgements}{Danksagungen}
730 \ProvideDictTranslation{advisor}{Betreuer}
731 \ProvideDictTranslation{Advisor}{Betreuer}
732 \ProvideDictTranslation{advisors}{Betreuer}
733 \ProvideDictTranslation{Advisors}{Betreuer}
734 \ProvideDictTranslation{co-advisor}{Mitbetreuer}
735 \ProvideDictTranslation{Co-advisor}{Mitbetreuer}
736 \ProvideDictTranslation{co-advisors}{Mitbetreuer}
737 \ProvideDictTranslation{Co-advisors}{Mitbetreuer}
738 \ProvideDictTranslation{matrnumber}{Matrikelnummer}
739 \ProvideDictTranslation{Matrnumber}{Matrikelnummer}
740 \ProvideDictTranslation{supervisor}{Prüfer}
741 \ProvideDictTranslation{Supervisor}{Prüfer}
742 \ProvideDictTranslation{co-supervisor}{Zweitprüfer}
743 \ProvideDictTranslation{Co-supervisor}{Zweitprüfer}
744 \ProvideDictTranslation{external}{Externer Gutachter}
745 \ProvideDictTranslation{External}{Externer Gutachter}
746 \ProvideDictTranslation{degreeprogramme}{Studiengang}
747 \ProvideDictTranslation{Degreeprogramme}{Studiengang}
748 \ProvideDictTranslation{Bachelor-thesis}{Bachelorarbeit}
749 \ProvideDictTranslation{Bachelor-thesis-proposal}{Bachelorarbeitsproposal}
750 \ProvideDictTranslation{Master-thesis}{Masterarbeit}
751 \ProvideDictTranslation{Master-thesis-proposal}{Masterarbeitsproposal}
752 \ProvideDictTranslation{PhD-thesis}{Dissertation}
753 \ProvideDictTranslation{PhD-thesis-proposal}{Dissertationsproposal}
754 \ProvideDictTranslation{date}{Datum}
755 \ProvideDictTranslation{Date}{Datum}
756 \ProvideDictTranslation{university-of-passau}{Universität Passau}
757 \ProvideDictTranslation{up}{Universität Passau}
758 \ProvideDictTranslation{fim}{Fakultät für Informatik und Mathematik}
759 </german>
760 </translations>

4 se2colors implementation

Start the DocStrip guards.

```
761 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
762 <@=slcd_colors>
```

Identify the package and give the overall version information.

```
763 \ProvidesExplPackage {se2colors} {2026-04-03} {4.4.1}
```

```
764 {A colour support package for the se2thesis bundle}
```

4.1 Load-time options

`\l__slcd_colors_colormode_tl` Holds the colour mode selected by the user as a package load-time option.

```
765 \keys_define:nn { seiicolors }
766 {
767   cmode .choice:,
768   cmode / 4C .code:n = {
769     \PassOptionsToPackage{ cmyk }{ xcolor }
770     \tl_gset:Nn \l__slcd_colors_colormode_tl { 4C }
771   },
772   cmode / RGB .code:n = {
773     \PassOptionsToPackage{ rgb }{ xcolor }
774     \tl_gset:Nn \l__slcd_colors_colormode_tl { RGB }
775   },
776   cmode / BW .code:n = {
777     \PassOptionsToPackage{ gray }{ xcolor }
778     \tl_gset:Nn \l__slcd_colors_colormode_tl { BW }
779   },
780   cmode / CMYK .meta:n = { cmode=4C },
781   cmode / cmyk .meta:n = { cmode=4C },
782   cmode / rgb .meta:n = { cmode=RGB },
783   cmode / gray .meta:n = { cmode=BW },
784   cmode / bw .meta:n = { cmode=BW },
785   RGB .meta:n = { cmode=RGB },
786   rgb .meta:n = { cmode=RGB },
787   CMYK .meta:n = { cmode=4C },
788   cmyk .meta:n = { cmode=4C },
789   BW .meta:n = { cmode=BW },
790   bw .meta:n = { cmode=BW },
791   gray .meta:n = { cmode=BW },
792 }
793 \keys_set:nn { seiicolors } { cmode = 4C }
```

(End of definition for `\l__slcd_colors_colormode_tl`.)

4.2 Option handling

```
794 \IfFormatAtLeastTF { 2022-06-01 }
795 { \ProcessKeyOptions [ seiicolors ] }
796 {
797   \RequirePackage { l3keys2e }
```

```

798 \ProcessKeysOptions { seiicolors }
799 }

```

4.3 Colour definitions

Load the xcolor package for colour definitions.

```

800 \RequirePackage{ xcolor }

```

Define the primary colours gray and orange as given by the University of Passau's style guides.

```

801 \definecolorset[named]{ RGB/cmyk } { UPSE2- } {} {%
802   Orange,242,148,0/0.00,0.44,0.95,0.01;%
803   Gray,153,159,158/0.40,0.28,0.28,0.00;%
804   JUR,229,49,56/0.01,0.90,0.81,0.01;%
805   WIWI,0,96,57/0.87,0.20,0.87,0.36;%
806   PHIL,188,42,51/0.06,0.93,0.81,0.11;%
807   FIM,0,90,161/0.93,0.63,0.01,0.02;%
808   DarkGray,77,77,77/0.74,0.67,0.62,0.18;%
809   White,255,255,255/0.00,0.00,0.00,0.00;%
810   MediumGray,127,127,127/0.52,0.43,0.40,0.02;%
811   LightGray,229,229,229/0.08,0.06,0.04,0.00;%
812   LightRed,229,49,56/0.01,0.90,0.81,0.01;%
813   DarkRed,188,42,51/0.06,0.93,0.80,0.11;%
814   Green,0,96,57/0.87,0.20,0.86,0.35;%
815   Blue,0,90,161/0.93,0.63,0.01,0.02;%
816   AccentGray,153,159,158/0.40,0.28,0.28,0.00%
817 }

```

Define the derived colours.

```

818 \colorlet{ UPSE2-DarkGray1 } { UPSE2-DarkGray!20!white }
819 \colorlet{ UPSE2-DarkGray2 } { UPSE2-DarkGray!40!white }
820 \colorlet{ UPSE2-DarkGray3 } { UPSE2-DarkGray!60!white }
821 \colorlet{ UPSE2-DarkGray4 } { UPSE2-DarkGray!75!black }
822 \colorlet{ UPSE2-DarkGray5 } { UPSE2-DarkGray!50!black }
823 \colorlet{ UPSE2-White1 } { UPSE2-White!95!black }
824 \colorlet{ UPSE2-White2 } { UPSE2-White!85!black }
825 \colorlet{ UPSE2-White3 } { UPSE2-White!75!black }
826 \colorlet{ UPSE2-White4 } { UPSE2-White!65!black }
827 \colorlet{ UPSE2-White5 } { UPSE2-White!50!black }
828 \colorlet{ UPSE2-MediumGray1 } { UPSE2-MediumGray!20!white }
829 \colorlet{ UPSE2-MediumGray2 } { UPSE2-MediumGray!40!white }
830 \colorlet{ UPSE2-MediumGray3 } { UPSE2-MediumGray!60!white }
831 \colorlet{ UPSE2-MediumGray4 } { UPSE2-MediumGray!75!black }
832 \colorlet{ UPSE2-MediumGray5 } { UPSE2-MediumGray!50!black }
833 \colorlet{ UPSE2-LightGray1 } { UPSE2-LightGray!90!black }
834 \colorlet{ UPSE2-LightGray2 } { UPSE2-LightGray!75!black }
835 \colorlet{ UPSE2-LightGray3 } { UPSE2-LightGray!55!black }
836 \colorlet{ UPSE2-LightGray4 } { UPSE2-LightGray!25!black }
837 \colorlet{ UPSE2-LightGray5 } { UPSE2-LightGray!10!black }
838 \colorlet{ UPSE2-Orange1 } { UPSE2-Orange!20!white }
839 \colorlet{ UPSE2-Orange2 } { UPSE2-Orange!40!white }
840 \colorlet{ UPSE2-Orange3 } { UPSE2-Orange!60!white }
841 \colorlet{ UPSE2-Orange4 } { UPSE2-Orange!75!black }
842 \colorlet{ UPSE2-Orange5 } { UPSE2-Orange!50!black }
843 \colorlet{ UPSE2-LightRed1 } { UPSE2-LightRed!20!white }

```



```

844 \colorlet{ UPSE2-LightRed2 } { UPSE2-LightRed!40!white }
845 \colorlet{ UPSE2-LightRed3 } { UPSE2-LightRed!60!white }
846 \colorlet{ UPSE2-LightRed4 } { UPSE2-LightRed!75!black }
847 \colorlet{ UPSE2-LightRed5 } { UPSE2-LightRed!50!black }
848 \colorlet{ UPSE2-DarkRed1 } { UPSE2-DarkRed!20!white }
849 \colorlet{ UPSE2-DarkRed2 } { UPSE2-DarkRed!40!white }
850 \colorlet{ UPSE2-DarkRed3 } { UPSE2-DarkRed!60!white }
851 \colorlet{ UPSE2-DarkRed4 } { UPSE2-DarkRed!75!black }
852 \colorlet{ UPSE2-DarkRed5 } { UPSE2-DarkRed!50!black }
853 \colorlet{ UPSE2-Green1 } { UPSE2-Green!10!white }
854 \colorlet{ UPSE2-Green2 } { UPSE2-Green!25!white }
855 \colorlet{ UPSE2-Green3 } { UPSE2-Green!50!white }
856 \colorlet{ UPSE2-Green4 } { UPSE2-Green!75!white }
857 \colorlet{ UPSE2-Green5 } { UPSE2-Green!90!white }
858 \colorlet{ UPSE2-Blue1 } { UPSE2-Blue!20!white }
859 \colorlet{ UPSE2-Blue2 } { UPSE2-Blue!40!white }
860 \colorlet{ UPSE2-Blue3 } { UPSE2-Blue!60!white }
861 \colorlet{ UPSE2-Blue4 } { UPSE2-Blue!75!black }
862 \colorlet{ UPSE2-Blue5 } { UPSE2-Blue!50!black }
863 \colorlet{ UPSE2-AccentGray1 } { UPSE2-AccentGray!20!white }
864 \colorlet{ UPSE2-AccentGray2 } { UPSE2-AccentGray!40!white }
865 \colorlet{ UPSE2-AccentGray3 } { UPSE2-AccentGray!60!white }
866 \colorlet{ UPSE2-AccentGray4 } { UPSE2-AccentGray!75!black }
867 \colorlet{ UPSE2-AccentGray5 } { UPSE2-AccentGray!50!black }
868 </package>

```

5 se2fonts implementation

Start the DocStrip guards.

```
869 <*package>
```

Identify the internal prefix (L^AT_EX3 DocStrip convention): only internal material in this *submodule* should be used directly.

```
870 <@@=slcd_fonts>
```

Identify the package and give the overall version information.

```
871 \ProvidesExplPackage {se2fonts} {2026-04-03} {4.4.1}
```

```
872 {A font-selection support package for the se2thesis bundle}
```

5.1 Load-time options

The package does not have any load-time options; the formerly defined option to set the font mode was removed with se2thesis version 4.0.0.

5.2 Helper macros

Define a warning message of users of pdfL^AT_EX that not all features of the fonts are available and that they should consider using LuaT_EX instead.

```
873 \msg_new:nnnn { seiifonts } { pdflatex-used }
874 { You~ are~ using~ pdfLaTeX~ with~ the~ se2fonts~ packages.}
875 {
876   While~ this~ works~ some~ font~ features~ are~ not~ available,~ consider~
877   using~ luatex~ instead.
878 }
```

\pdftexengine We define several alias macros to identify which engine the user is running.

```
\xetexengine 879 \cs_new_eq:NN \pdftexengine \sys_if_engine_pdfptex_p:
\luatexengine 880 \cs_new_eq:NN \xetexengine \sys_if_engine_xetex_p:
881 \cs_new_eq:NN \luatexengine \sys_if_engine_luatex_p:
```

(End of definition for `\pdftexengine`, `\xetexengine`, and `\luatexengine`. These functions are documented on page 10.)

\ifengineTF True, if the engine used matches the given first argument.

```
\ifengineT 882 \NewExpandableDocumentCommand \ifengineTF { mmm }
\ifengineF 883 {
884   \bool_if:nTF { #1 } { #2 } { #3 }
885 }
886 \NewExpandableDocumentCommand \ifengineT { mm }
887 {
888   \bool_if:nT { #1 } { #2 }
889 }
890 \NewExpandableDocumentCommand \ifengineF { mm }
891 {
892   \bool_if:nF { #1 } { #2 }
893 }
```

(End of definition for `\ifengineTF`, `\ifengineT`, and `\ifengineF`. These functions are documented on page 10.)

The package is not tested with Xe_ΛTeX, thus we provide an error to the user and stop the execution if they want to use the package with Xe_ΛTeX.

```

894 \ifengineT { \xetexengine }
895 {
896   \msg_new:nnnn { seiifonts } { xetex-not-supported }
897   { XeTeX~ is~ not~ supported~ by~ the~ se2fonts~ package. }
898   { Switch~ to~ pdfTeX~ or~ (preferably)~ LuaTeX. }
899   \msg_error:nn { seiifonts } { xetex-not-supported }
900 }

```

5.3 Font loading

Load the `mismath` package, which itself loads `mathtools` and transitively `amsmath` *before* `unicode-math`.

```

901 \RequirePackage { mismath }

```

Depending on the engine used by the user, we can use `fontspec` for loading fonts.

```

902 \ifengineTF { \luatexengine }
903 {

```

If the user uses Lua_ΛTeX, load `fontspec` and `unicode-math`.

```

904   \RequirePackage { fontspec }
905   \PassOptionsToPackage { math-style=ISO, bold-style=ISO } { unicode-math }
906   \RequirePackage { unicode-math }

```

To make sure the scaling of the fonts matches, we let `fontspec` do this matching based on the lower-case characters.

```

907   \defaultfontfeatures { Scale = MatchLowercase }
908   \defaultfontfeatures [ \rmfamily ] { Scale = 1 }

```

Load the respective `libertinus-otf` package and omit the monospaced font.

```

909   \PassOptionsToPackage { mono=false } { libertinus-otf }
910   \RequirePackage { libertinus-otf }

```

Load the *Inconsolata Nerd Font* monospaced font.

```

911   \RequirePackage { inconsolata-nerd-font }
912 } {

```

The user does not use Lua_ΛTeX, thus fallback to T1 fonts.

```

913   \msg_warning:nn { seiifonts } { pdflatex-used }
914   \PassOptionsToPackage { T1 } { fontenc }
915   \PassOptionsToPackage { scaled=0.9, varl } { inconsolata }
916   \PassOptionsToPackage { mono=false } { libertinus-type1 }
917   \RequirePackage { fontenc }
918   \RequirePackage { inconsolata }
919   \RequirePackage { libertinus-type1 }
920 }

```

```

921 \</package>

```

6 se2packages implementation

Start the DocStrip guards.

```
922 <*package>
```

Identify the internal prefix (L^AT_EX DocStrip convention): only internal material in this *submodule* should be used directly.

```
923 <@@=slcd_packages>
```

Identify the package and give the overall version information.

```
924 \ProvidesExplPackage {se2packages} {2026-04-03} {4.4.1}
```

```
925 {Supporting packages for the se2thesis bundle}
```

6.1 Load-time options

Before we define the actual options, define some Boolean variables to store the selected values.

```
\l_slcd_packages_csquotes_bool Whether or not to load csquotes.
```

```
926 \bool_new:N \l_slcd_packages_csquotes_bool
```

(End of definition for \l_slcd_packages_csquotes_bool.)

```
\l_slcd_packages_booktabs_bool Whether or not to load booktabs.
```

```
927 \bool_new:N \l_slcd_packages_booktabs_bool
```

(End of definition for \l_slcd_packages_booktabs_bool.)

```
\l_slcd_packages_siunitx_bool Whether or not to load and configure siunitx.
```

```
928 \bool_new:N \l_slcd_packages_siunitx_bool
```

(End of definition for \l_slcd_packages_siunitx_bool.)

```
\l_slcd_packages_minted_bool Whether or not to load and configure minted.
```

```
929 \bool_new:N \l_slcd_packages_minted_bool
```

(End of definition for \l_slcd_packages_minted_bool.)

```
\l_slcd_packages_listings_bool Whether or not to load and configure listings.
```

```
930 \bool_new:N \l_slcd_packages_listings_bool
```

(End of definition for \l_slcd_packages_listings_bool.)

```
\l_slcd_packages_biblatex_tl Whether or not to load and configure biblatex.
```

```
931 \tl_new:N \l_slcd_packages_biblatex_tl
```

(End of definition for \l_slcd_packages_biblatex_tl.)

```
\l_slcd_packages_selnolig_bool Whether or not to load selnolig (LuaTEX only).
```

```
932 \bool_new:N \l_slcd_packages_selnolig_bool
```

(End of definition for \l_slcd_packages_selnolig_bool.)

```
\l_slcd_packages_luawindowcontrol_bool Whether or not to load luawindowcontrol (LuaTEX only).
```

```
933 \bool_new:N \l_slcd_packages_luawindowcontrol_bool
```

(End of definition for \l_slcd_packages_luawindowcontrol_bool.)

`\l__slcd_packages_microtype_bool` Whether or not to load microtype.

934 `\bool_new:N \l__slcd_packages_microtype_bool`

(End of definition for `\l__slcd_packages_microtype_bool`.)

`\l__slcd_packages_cleveref_bool` Whether or not to load and configure cleveref.

935 `\bool_new:N \l__slcd_packages_cleveref_bool`

(End of definition for `\l__slcd_packages_cleveref_bool`.)

`\l__slcd_packages_all_bool` Whether or not to load and configure all recommended packages.

936 `\bool_new:N \l__slcd_packages_all_bool`

(End of definition for `\l__slcd_packages_all_bool`.)

Define the actual load-time options.

937 `\keys_define:nn { seiipackages }`

938 `{`

939 `csquotes .bool_gset:N = \l__slcd_packages_csquotes_bool,`

940 `csquotes .initial:n = true,`

941 `nocsquotes .meta:n = { csquotes=false },`

942

943 `booktabs .bool_gset:N = \l__slcd_packages_booktabs_bool,`

944 `booktabs .initial:n = true,`

945 `nobooktabs .meta:n = { booktabs=false },`

946

947 `siunitx .bool_gset:N = \l__slcd_packages_siunitx_bool,`

948 `siunitx .initial:n = false,`

949

950 `minted .bool_gset:N = \l__slcd_packages_minted_bool,`

951 `minted .initial:n = false,`

952

953 `listings .bool_gset:N = \l__slcd_packages_listings_bool,`

954 `listings .initial:n = false,`

955

956 `biblatex .tl_gset:N = \l__slcd_packages_biblatex_tl,`

957 `biblatex .initial:n = false,`

958

959 `selnolig .bool_gset:N = \l__slcd_packages_selnolig_bool,`

960 `selnolig .initial:n = true,`

961 `noselnolig .meta:n = { selnolig=false },`

962

963 `widowcontrol .bool_gset:N = \l__slcd_packages_luawidowcontrol_bool,`

964 `widowcontrol .initial:n = false,`

965 `nowidowcontrol .meta:n = { widowcontrol=false },`

966

967 `microtype .bool_gset:N = \l__slcd_packages_microtype_bool,`

968 `microtype .initial:n = true,`

969 `nomicrotype .meta:n = { microtype=false },`

970

971 `cleveref .bool_gset:N = \l__slcd_packages_cleveref_bool,`

972 `cleveref .initial:n = false,`

973

974 `all .bool_gset:N = \l__slcd_packages_all_bool,`

975 `all .initial:n = false,`

976 `}`

6.2 Option handling

```
977 \IfFormatAtLeastTF { 2022-06-01 }
978 { \ProcessKeyOptions [ seiipackages ] }
979 {
980   \RequirePackage{ l3keys2e }
981   \ProcessKeysOptions { seiipackages }
982 }
```

Define an error message if both minted and listings are requested.

```
983 \msg_set:nnnn { seiipackages } { conflicting-packages }
984 { Setting~ both~ minted~ and~ listings~ to~ true~ is~ not~ possible. }
985 { Choose~ either~ of~ them! }
```

Define a message for logging that a specific package will be loaded by se2packages. Expects as parameter the name of the package that will be loaded.

```
986 \msg_new:nnn { seiipackages } { load-package }
987 { se2packages~ loads~ the~ #1~ package now. }
```

And, in case both values are set to true, raise the error message.

```
988 \bool_lazy_and:nnT { \l__slcd_packages_minted_bool }
989 { \l__slcd_packages_listings_bool }
990 {
991   \msg_error:nn { seiipackages } { conflicting-packages }
992 }
```

In case the all option is set, set all other values to true.

```
993 \bool_if:NT \l__slcd_packages_all_bool
994 {
995   \bool_gset_true:N \l__slcd_packages_csquotes_bool
996   \bool_gset_true:N \l__slcd_packages_booktabs_bool
997   \bool_gset_true:N \l__slcd_packages_siunitx_bool
998   \bool_gset_true:N \l__slcd_packages_minted_bool
999   \bool_gset_false:N \l__slcd_packages_listings_bool
1000   \bool_gset_true:N \l__slcd_packages_selnolig_bool
1001   \bool_gset_true:N \l__slcd_packages_luawindowcontrol_bool
1002   \bool_gset_true:N \l__slcd_packages_microtype_bool
1003   \tl_gset:Nn \l__slcd_packages_biblatex_bool { true }
1004   \bool_gset_true:N \l__slcd_packages_cleveref_bool
1005 }
```

6.3 Package loading

Conditionally load the csquotes package.

```
1006 \bool_if:NT \l__slcd_packages_csquotes_bool
1007 {
1008   \msg_info:nnn { seiipackages } { load-package } { csquotes }
1009   \RequirePackage { fvextra }
1010   \RequirePackage { csquotes }
1011 }
```

Conditionally load the booktabs package.

```
1012 \bool_if:NT \l__slcd_packages_booktabs_bool
1013 {
1014   \msg_info:nnn { seiipackages } { load-package } { booktabs }
1015   \RequirePackage { booktabs }
1016 }
```

Conditionally load and configure the siunitx package.

```

1017 \bool_if:NT \l__slcd_packages_siunitx_bool
1018 {
1019   \msg_info:nnn { seiipackages } { load-package } { siunitx }
1020   \RequirePackage [
1021     add-integer-zero=false,
1022     free-standing-units=true,
1023     group-minimum-digits=4,
1024     list-final-separator={ ,~ and~ },
1025     round-mode=figures,
1026     round-precision=3,
1027     separate-uncertainty=true,
1028     uncertainty-mode=separate,
1029     mode=match,
1030   ] { siunitx }
1031 }

```

Conditionally load and configure the minted package.

```

1032 \bool_if:NT \l__slcd_packages_minted_bool
1033 {
1034   \msg_info:nnn { seiipackages } { load-package } { minted }
1035   \RequirePackage [ newfloat=true ] { minted }
1036   \setminted {
1037     autogobble,
1038     breaklines=true,
1039     fontsize=\footnotesize,
1040     frame=single,
1041     linenos=false,
1042     resetmargins=true,
1043     xleftmargin=1em,
1044     xrightmargin=1em,
1045   }
1046 }

```

Conditionally load and configure the listings package.

```

1047 \bool_if:NT \l__slcd_packages_listings_bool
1048 {
1049   \msg_info:nnn { seiipackages } { load-package } { listings }
1050   \RequirePackage { listings }
1051   \lstset{
1052     basicstyle=\footnotesize\ttfamily,
1053     breaklines=true,
1054     captionpos=t,
1055     extendedchars=true,
1056     frame=single,
1057     keywordstyle=\color { blue }\bfseries,
1058     showspaces=false,
1059     showtabs=false,
1060     showstringspaces=false,
1061     tabsize=2,
1062   }
1063 }

```

Conditionally load selnolig if present and we run Lua \TeX .

```

1064 \bool_lazy_and:nnT { \l__slcd_packages_selnolig_bool }

```

```

1065 { \sys_if_engine luatex_p: }
1066 {
1067   \IfFileExists { selnolig.sty }
1068   {
1069     \RequirePackage { selnolig }
1070   } {
1071     \msg:nnnn { seiipackages }
1072       { selnolig-not-available }
1073       { Could~ not~ find~ selnolig.sty }
1074       { You~ might~ want~ to~ install~ it~ for~ better~ ligatures~ control.}
1075     \msg_note:nn { seiipackages } { selnolig-not-available }
1076   }
1077 }

```

Conditionally load luawidowcontrol if present and we run LuaTeX.

```

1078 \bool_lazy_and:nnT { \l__slcd_packages_luawidowcontrol_bool }
1079 { \sys_if_engine luatex_p: }
1080 {
1081   \IfFileExists { lua-widow-control.sty }
1082   {
1083     \RequirePackage { lua-widow-control }
1084   } {
1085     \msg:nnnn { seiipackages }
1086       { lua-widow-control-not-available }
1087       { Could~ not~ find~ lua-widow-control.sty }
1088       {
1089         You~ might~ want~ to~ install~ it~ for~ better~ control~ over~
1090         widows~ and~ orphans.
1091       }
1092     \msg_note:nn { seiipackages } { lua-widow-control-not-available }
1093   }
1094 }

```

Conditionally load and configure microtype. If a package option requires for the lua-widow-control package, we do not set penalties for widows and orphans but let that package control these penalties.

```

1095 \bool_if:NT \l__slcd_packages_microtype_bool
1096 {
1097   \msg_info:nnn { seiipackages } { load-package } { microtype }
1098   \RequirePackage { microtype }
1099   \bool_if:NF \l__slcd_packages_luawidowcontrol_bool
1100   {
1101     \clubpenalty=10000
1102     \widowpenalty=10000
1103     \displaywidowpenalty=10000
1104   }
1105   \SetExtraKerning{
1106     encoding = { OT1,T1,T2A,LY1,OT4,QX,T5,TS1,EU1,EU2 }
1107   } {
1108     \textendash = { 167,167 },
1109     - = { 167,167 }
1110   }
1111 }

```

Conditionally load and configure the biblatex package.


```

1112 \tl_if_eq:NnT \l__slcd_packages_biblatex_tl {alphabetic}
1113 {
1114   \msg_info:nnn { seiipackages } { load-package } { biblatex }
1115   \PassOptionsToPackage
1116     {
1117       backend=biber,
1118       backref=true,
1119       datamodel=software,
1120       giveninits=true,
1121       hyperref=auto,
1122       maxnames=100,
1123       minalphanames=3,
1124       sorting=nyt,
1125       style=alphabetic,
1126     } { biblatex }
1127   \RequirePackage { biblatex }
1128   \RequirePackage { software-biblatex }
1129   \ExecuteBibliographyOptions {
1130     halid=false,
1131     swhid=true,
1132     shortswid=false,
1133     swlabels=true,
1134     vcs=true,
1135     license=true,
1136   }
1137 }
1138
1139 \bool_new:N \l__slcd_packages_biblatex_numeric_variants_bool
1140 \tl_if_eq:NnT \l__slcd_packages_biblatex_tl { true }
1141 {
1142   \bool_gset_true:N \l__slcd_packages_biblatex_numeric_variants_bool
1143 }
1144 \tl_if_eq:NnT \l__slcd_packages_biblatex_tl { numeric }
1145 {
1146   \bool_gset_true:N \l__slcd_packages_biblatex_numeric_variants_bool
1147 }
1148
1149 \bool_if:NT \l__slcd_packages_biblatex_numeric_variants_bool
1150 {
1151   \msg_info:nnn { seiipackages } { load-package } { biblatex }
1152   \PassOptionsToPackage
1153     {
1154       backend=biber,
1155       backref=true,
1156       citereset=chapter+,
1157       citetracker=context,
1158       giveninits=true,
1159       hyperref=auto,
1160       sorting=nyt,
1161       datamodel=acmdatamodel,
1162       style=acmnumeric,
1163     } { biblatex }
1164   \RequirePackage { biblatex }
1165   \RequirePackage { ragged2e }

```

```

1166 \RequirePackage [ mark=arabic,shape=up,Ragged ] { sidenotesplus }
1167
1168 \newbibmacro { cite:authoryear }
1169 {
1170   \printtext [ labelnumberwidth ] {
1171     \usebibmacro { cite }
1172   }
1173   \setunit { \addspace }
1174   \printnames { labelname }
1175   \setunit { \labelnamepunct }\newblock%
1176   \usebibmacro { year }%
1177   \newunit%
1178   \printfield [ title ] { labeltitle }
1179 }
1180
1181 \newrobustcmd* { \makebibmarginnote } [ 1 ]
1182 {
1183   \sidenote* { \blxmkbibnote { foot } { #1 } }
1184 }
1185
1186 \DeclareCiteCommand { \maycite } [ \makebibmarginnote ]
1187 { \usebibmacro { prenote } }
1188 {
1189   \usebibmacro { citeindex }%
1190   \usebibmacro { cite:authoryear }
1191 }
1192 { \multicitedelim }
1193 { \usebibmacro { postnote } }
1194
1195 \newcommand* { \cbx@savedcites } {}
1196
1197 \newcommand* { \cbx@margcitewrap } [ 1 ]
1198 {%
1199   \global\let\cbx@savedcites\empty
1200   \mkbibbrackets { #1 }%
1201   \cbx@savedcites
1202 }
1203
1204 \DeclareCiteCommand { \margincite } [ \cbx@margcitewrap ]
1205 { \usebibmacro { prenote } }
1206 {
1207   \usebibmacro { citeindex }%
1208   \usebibmacro { cite }%
1209   \ifciteseen
1210   {}
1211   {
1212     \xappto\cbx@savedcites {
1213       \noexpand\maycite {
1214         \thefield { entrykey }
1215       }
1216     }
1217   }
1218 }
1219 { \multicitedelim }

```

```

1220     { \usebibmacro { postnote } }
1221
1222     \DeclareMultiCiteCommand { \margincites } [ \cbx@margcitewrap ]
1223     { \margincite } { \multicitedelim }
1224
1225     \DeclareAutoCiteCommand { margin } { \margincite } { \margincites }
1226     \ExecuteBibliographyOptions { autocite=margin }
1227     \newcommand { \bibliofont } { \footnotesize }
1228     \DeclareFieldFormat { titlecase } { #1 }% Preserve title capitalisation
1229 }

```

Conditionally load the cleveref package as the last of the preamble.

```

1230 \bool_if:NT \l__slcd_packages_cleveref_bool
1231 {
1232     \msg_info:nnn { seiipackages } { load-package } { cleveref }
1233     \AddToHook { begindocument/before }
1234     {
1235         \RequirePackage [ capitalise ] { cleveref }
1236         \Crefname { resq } { Research Question } { Research Questions }
1237         \Crefname { hyp } { Hypothesis } { Hypotheses }
1238     }
1239 }
1240 </package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols		
\&	300	\areaset 213, 217
\,	405, 431	\author 4–6, 21, 291
\\	404, 405, 406, 407, 408, 409, 410, 411, 412, 417, 418, 419, 420, 421, 422, 423, 424, 425, 430, 431, 432, 433, 434, 435, 436, 437, 438, 466, 470, 474, 478, 482, 486, 506, 508, 510, 644, 649	\authorshipDeclaration 6, 599
\\	29	\autocite 14
_	33, 36, 39, 226, 239, 453, 671	\autodot 526
A		B
abstract (env.)	5, 548	\backmatter 6, 588
\abstract	5, 30, 547	\baselineskip 335, 534
acknowledgements (env.)	6, 565	\begin 234, 250, 258, 270, 315, 351, 355, 401, 462, 463, 630, 664, 680
\addspace	1173	\begingroup 326
\AddToDoHook	544	\bfseries 520, 669, 1057
\AddToHook	1233	biblatex 14
\addtokomafont	520, 521, 522, 523	\bibliofont 1227
\advisor	4, 164	\bigskip 393, 397, 461, 531, 640
all	15	\blxmkbibnote 1183
\and	5, 293	booktabs 13
		bool commands:
		\bool_gset_false:N 999
		\bool_gset_true:N 995, 996, 997, 998, 1000, 1001, 1002, 1004, 1142, 1146

\bool_if:NTF	993, 1006, 1012, 1017, 1032, 1047, 1095, 1099, 1149, 1230
\bool_if:nTF	884, 888, 892
\bool_lazy_and:nnTF	988, 1064, 1078
\bool_new:N	926, 927, 928, 929, 930, 932, 933, 934, 935, 936, 1139
\bottomrule	12
box commands:	
\box_ht:N	309, 377, 379
\box_if_exist:NTF	198, 364
\box_new:N	200, 366
\box_use:N	310, 378
\box_wd:N	306, 308
C	
\caption	12
\centering	388, 391, 395, 493, 648
\chapter	560, 576, 626
\chapterformat	524
\chapterlinesformat	529
\chapterlineswithprefixformat	535
class	3
\cleardoubleoddpages	584, 590, 596
\cleardoublepages	644
\clearpage	361, 557, 584, 590, 596
\clearpaairofpagestyles	223
cleveref	14
clist commands:	
\clist_map_inline:nn	126
\clubpenalty	1101
cmode	8
\coadvisor	4, 164
\color	230, 242, 246, 264, 276, 281, 526, 1057
\colorlet	818, 819, 820, 821, 822, 823, 824, 825, 826, 827, 828, 829, 830, 831, 832, 833, 834, 835, 836, 837, 838, 839, 840, 841, 842, 843, 844, 845, 846, 847, 848, 849, 850, 851, 852, 853, 854, 855, 856, 857, 858, 859, 860, 861, 862, 863, 864, 865, 866, 867
colormode	3
\columnwidth	339
\cosupervisor	4, 156
\coverpagebottommargin	332
\coverpagerightmargin	306
\coverpagetopmargin	307, 327, 332
\Crefname	1236, 1237
cs commands:	
\cs_if_exist:NTF	133
\cs_new:Nn	385
\cs_new_eq:NN	879, 880, 881
csquotes	13
D	
\DeclareAutoCiteCommand	1225
\DeclareCiteCommand	1186, 1204
\DeclareFieldFormat	1228
\DeclareMultiCiteCommand	1222
\DeclareNewLayer	303
\DeclareNewPageStyleByLayers	312
\DeclareTranslation	35, 38
\DeclareTranslationFallback	32
\def	317
\defaultfontfeatures	907, 908
\definecolorset	801
\degreeprogramme	4, 27, 148
\department	4, 27, 172
\dictumwidth	546
dim commands:	
\dim_gset:Nn	65, 66, 67, 68, 69, 70, 71, 193, 195
\dim_if_exist:NTF	188
\dim_new:N	58, 59, 60, 61, 62, 63, 64, 190
\dimexpr	327, 328, 329, 330, 331
\displaywidowpenalty	1103
E	
\edef	318
\else	361, 390, 584, 590, 596
\emph	509
\empty	1199
\end	236, 252, 260, 272, 353, 357, 362, 461, 488, 489, 639, 675, 680
\endgroup	319
\endinput	14
\enskip	525
environments:	
abstract	5, 548
acknowledgements	6, 565
hyp	7, 658
resq	7, 658
summary	7, 661
\evensidemargin	329
\ExecuteBibliographyOptions	1129, 1226
exp commands:	
\exp_args:NNV	500
\ExplFileDate	17
\ExplLoaderFileDate	5
\ExplSyntaxOff	661
\ExplSyntaxOn	677
\external	4, 180
F	
\fi	359, 360, 361, 392, 584, 590, 596
\fmtversion	16
\fnsymbol	317
\footnotesize	227, 240, 257, 261, 269, 273, 1039, 1052, 1227

\footskip 335
 \frontmatter 6, [582](#)

G

\GetTranslation 300, 442,
 444, 446, 448, 450, 466, 470, 474, 478,
 482, 486, 496, 512, 514, 516, 517, 561, 577
 \global 320, 321, 322, 323, 1199
 group commands:

 \group_begin: 226,
 229, 239, 241, 245, 263, 275, 280, 299,
 369, 387, 394, 491, 505, 507, 550, 567, 602
 \group_end: 226,
 232, 239, 243, 248, 266, 278, 282, 301,
 380, 389, 396, 498, 510, 518, 563, 579, 643

H

hbox commands:

 \hbox_gset:Nn 204, 372
 \headheight 333
 \headingdot 544, 545
 \headmark 242, 281
 \headsep 334
 \hfill 641
 \hline 12
 \hrule 532
 \hrulefill 530
 \hsize 340, 341
 \hspace 228, 233,
 237, 244, 249, 253, 256, 262, 268, 274, 279
 \ht 307
 \Huge 285
 hyp (env.) 7, [658](#)

I

\ifciteseen 1209
 \ifengineF 10, [882](#)
 \ifengineT 10, [882](#), 894
 \ifengineTF 10, [882](#), 902
 \IfFileExists 1067, 1081
 \IfFormatAtLeastTF 2, [16](#), 115, 794, 977
 \IfNoValueF 551, 568, 604
 \Ifstr 536
 \Iftocfeature 553, 558, 570, 574, 620, 624
 \ifx 361, 390
 \includegraphics 206
 \institute 4, 27, [172](#)
 int commands:
 \int_compare:nTF 191, 211
 \int_gset_eq:NN 82
 \int_new:N 41
 \item 631, 636
 \itshape 543

K

keys commands:

 \l_keys_choice_int 82
 \l_keys_choice_tl 107
 \keys_define:nn 72, 765, 937
 \l_keys_key_str 112
 \keys_set:nn 793
 \KOMAOption 137
 \KOMAOptions 136

L

\label 13
 \labelnamepunct 1175
 \Large 286
 \large 288, 522
 \lefoot 255
 \let 324, 358, 381, 508, 557, 1199
 \linewidth 341, 546, 649
 listings 14
 \LoadClass 130
 \LoadDictionary 31
 \location 5, 6, [184](#)
 logfile 3
 \lstset 1051
 \luatexengine 10, [879](#), 902

M

\mainmatter 6, [588](#)
 \makebibmarginnote 1181, 1186
 \makebox 649
 \maketitle 4, 25, 314
 \MakeUppercase 537, 541
 \margincite 1204, 1223, 1225
 \margincites 1222, 1225
 \marginparsep 214, 215, 218, 219
 \matrnumber 4, [152](#)
 \maycite 1186, 1213
 \mbox 525
 \mdseries 521, 522, 523
 \medskip 391, 490
 \MessageBreak 11
 microtype 14
 \midrule 12
 minted 13
 \mkbibbrackets 1200
 msg commands:
 \msg:nnnn 1071, 1085
 \msg_error:nn 899, 991
 \msg_info:nnn 1008, 1014,
 1019, 1034, 1049, 1097, 1114, 1151, 1232
 \msg_new:nnn 609, 986
 \msg_new:nnnn 873, 896
 \msg_note:nn 1075, 1092
 \msg_set:nnnn 983

\msg_warning:nn	616, 913	\ProcessKeysOptions	119, 798, 981
\multicitedelim	1192, 1219, 1223	prop commands:	
N			
\newbibmacro	1168	\prop_gput:Nnn	112
\newblock	1175	\prop_map_inline:Nn	121, 131
\newcommand	545, 646, 1195, 1197, 1227	\prop_new:N	43, 44
\NewDocumentCommand	599, 678	\providecommand	16, 547, 582, 588, 594
\NewDocumentEnvironment	565, 662	\ProvideDictionaryFor	685, 723
\NewExpandableDocumentCommand	882, 886, 890	\ProvideDictTranslation	686, 687, 688, 689, 690,
\newif	581	691, 692, 693, 694, 695, 696, 697, 698,	
\newrobustcmd	1181	699, 700, 701, 702, 703, 704, 705, 706,	
\newtheorem	33, 658, 659	707, 708, 709, 710, 711, 712, 713, 714,	
\newunit	1177	715, 716, 717, 718, 719, 720, 724, 725,	
nobooktabs	13	726, 727, 728, 729, 730, 731, 732, 733,	
nocsquotes	13	734, 735, 736, 737, 738, 739, 740, 741,	
\noexpand	319, 320, 321, 322, 323, 324, 1213	742, 743, 744, 745, 746, 747, 748, 749,	
\noindent	506, 641	750, 751, 752, 753, 754, 755, 756, 757, 758	
nomicrotype	14	\ProvideDocumentCommand	144, 148,
\normalfont	224, 543	152, 156, 160, 164, 168, 172, 176, 180, 184	
\normalsize	235, 251, 259, 271, 287, 289, 290, 523, 543	\ProvidesExplClass	20
noselnolig	14	\ProvidesExplPackage	763, 871, 924
nowidowcontrol	14	\putUL	310
\null	256, 268, 376	Q	
\num	11	\qty	11
O			
\oddsidemargin	328	\quad	463
P			
\PackageError	8	R	
\pagemark	235, 251, 259, 271	\raggedleft	259, 271, 520
\pagenumbering	586, 592	\RedeclareSectionCommand	534
\pagestyle	284	\ref	13
paper	3	\relax	324, 327, 328, 329, 330, 332, 361, 508, 557
\paperheight	332	\renewcommand	292, 298,
\paperwidth	306, 330	313, 314, 368, 504, 524, 529, 535, 540, 546	
\par	357, 388, 391, 395, 455,	\RenewDocumentEnvironment	548
456, 457, 461, 490, 497, 530, 531, 601, 639		\RequirePackage	3, 29, 30, 118, 141, 143,
\paragraph	30	222, 383, 656, 660, 797, 800, 901, 904,	
\parbox	374, 530, 647	906, 910, 911, 917, 918, 919, 980, 1009,	
\PassOptionsToClass	124, 127	1010, 1015, 1020, 1035, 1050, 1069, 1083,	
\PassOptionsToPackage	140, 221, 654, 769,	1098, 1127, 1128, 1164, 1165, 1166, 1235	
773, 777, 905, 909, 914, 915, 916, 1115, 1152		resq (env.)	7, 658
\pdfTeXengine	10, 879	\rmfamily	908
prg commands:		\rofoot	225
\prg_new_conditional:Nnn	22	\rule	231, 247, 265, 277, 408, 421, 434, 649
\prg_return_false:	27	S	
\prg_return_true:	26	\scalebox	526
\printfield	1178	\section	555, 559, 572, 575, 622, 625
\printnames	1174	\sectionlinesformat	540
\printtext	1170	\selectlanguage	551, 568, 603
\ProcessKeyOptions	116, 795, 978	selnolig	14
seq commands:			
\seq_gset_split:Nnn	293	S	
\seq_new:N	291	\scalebox	526
\seq_use:Nnnn	300	\section	555, 559, 572, 575, 622, 625

`\setcounter` 316
`\SetExtraKerning` 1105
`\setkomafont` 224, 285, 286, 287, 288, 289, 290, 543
`\setlength` 214, 215, 218, 219
`\setminted` 1036
`\setparsizes` 342, 370
`\setunit` 1173, 1175
`\sffamily` 224
`\sidenote` 1183
`\signatureBox` 6, 642, 646
`siunitx` 13
skip commands:
`\skip_vertical:n` 377, 379
slcd commands:
`\slcd_package_if_loaded:n` 22
`\slcd_package_if_loaded:nTF` 3, 22, 652
`\slcd_package_if_loaded:p:n` 3, 22
slcd internal commands:
`\l__slcd_advisor_tl` 45, 166, 476, 478
`\l__slcd_author_seq` 291, 293, 300
`\l__slcd_base_class_tl`
. 42, 72, 124, 127, 130, 133
`\l__slcd_clsopts_prop` 42, 121
`\l__slcd_coadvisor_tl` 45, 170, 480, 482
`\l__slcd_colormode_tl` 72, 140
`\l__slcd_colors_colormode_tl` 765
`\l__slcd_cosupervisor_tl` 45, 162, 472, 474
`\l__slcd_degreeprogramme_tl` 45, 150, 451, 453
`\l__slcd_department_tl` 45, 174, 456
`\l__slcd_external_tl` 45, 182, 484, 486
`\l__slcd_headmarkspace_dim` 58, 228, 279
`\l__slcd_institute_tl` 45, 178, 457
`\l__slcd_licensemodifier_tl` 72
`\l__slcd_licensetype_tl` 72
`\l__slcd_licenseversion_tl` 72
`\l__slcd_location_tl` 45, 186, 605, 607, 641
`\l__slcd_logo_box`
. 188, 306, 308, 309, 310, 377, 379
`\l__slcd_logo_height_dim` 188
`\l__slcd_logofile_tl` 45, 86, 202, 208
`\l__slcd_marginspace_dim` 58, 237, 253, 256, 268
`\l__slcd_matrnumber_tl` 45, 154, 464, 466
`\l__slcd_packages_all_bool` 936, 974, 993
`\l__slcd_packages_biblatex_bool` 1003
`\l__slcd_packages_biblatex_numeric_`
`variants_bool` 1139, 1142, 1146, 1149
`\l__slcd_packages_biblatex_tl`
. 931, 956, 1112, 1140, 1144
`\l__slcd_packages_booktabs_bool`
. 927, 943, 996, 1012
`\l__slcd_packages_cleveref_bool`
. 935, 971, 1004, 1230
`\l__slcd_packages_csquotes_bool`
. 926, 939, 995, 1006
`\l__slcd_packages_listings_bool`
. 930, 953, 989, 999, 1047
`\l__slcd_packages_luawindowcontrol_bool`
. 933, 963, 1001, 1078, 1099
`\l__slcd_packages_microtype_bool`
. 934, 967, 1002, 1095
`\l__slcd_packages_minted_bool`
. 929, 950, 988, 998, 1032
`\l__slcd_packages_selnolig_bool`
. 932, 959, 1000, 1064
`\l__slcd_packages_siunitx_bool`
. 928, 947, 997, 1017
`\l__slcd_pagemark_minipage_dim`
. 58, 234, 250, 258, 270
`\l__slcd_paper_int` 41, 72, 191, 211
`\l__slcd_print_title:` 374, 385
`\l__slcd_ruleraise_dim` 58, 231, 247, 265, 277
`\l__slcd_rulespace_dim`
. 58, 233, 244, 249, 262, 274
`\l__slcd_rulethickness_dim`
. 58, 231, 247, 265, 277
`\l__slcd_rulewidth_dim` 58, 231, 247, 265, 277
`\l__slcd_signature_tl` 45, 295, 296, 629, 642
`\l__slcd_supervisor_tl` 45, 158, 468, 470
`\l__slcd_thesis_type_tl` 72, 402, 415,
428, 441, 443, 445, 447, 449, 511, 513, 515
`\l__slcd_title_box` 364, 372, 378
`\l__slcd_title_tl` 384, 399, 502
`\l__slcd_unknown_clsopts_prop` 42, 72, 131
`\l__slcd_version_tl` 33, 36, 39, 45, 146, 494
`\smallskip` 497
`\strut` 644
`\strutbox` 307
`\subsection` 554, 571, 621
`summary (env.)` 7, 661
`\summarybox` 678
`summarybox` 33
`\supervisor` 4, 156
sys commands:
`\sys_if_engine luatex_p:` 10, 881, 1065, 1079
`\sys_if_engine pdftex_p:` 10, 879
`\sys_if_engine xetex_p:` 10, 880

T

`\tabcaption` 12, 15
TeX and L^AT_EX 2_ε commands:
`\@author` 5, 291, 395, 506
`\@colht` 320, 336
`\@colroom` 321, 337
`\@date` 33, 36, 39, 495, 641
`\@empty` 358, 381, 390
`\@ifl@t@r` 5, 16
`\@ifpackagelater` 17
`\@ifpackageloaded` 17

<code>\ifundefined</code>	2	<code>\tl_gset_eq:NN</code>	107
<code>\@lowertitleback</code>	5, 29, 356, 504	<code>\tl_if_empty:N</code>	202, 451, 456, 457, 464, 468, 472, 476, 480, 484, 494, 607
<code>\@mainmatterfalse</code>	585, 597	<code>\tl_if_empty:nTF</code>	123, 135, 294
<code>\@mainmattertrue</code>	581, 591	<code>\tl_if_eq:NnTF</code> ..	402, 415, 428, 441, 443, 445, 447, 449, 511, 513, 515, 1112, 1140, 1144
<code>\@maketitle</code>	4, 26, 345, 368	<code>\tl_new:N</code>	42, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 384, 931
<code>\@plus</code>	342, 370	<code>\tl_set:Nn</code>	146, 150, 154, 158, 162, 166, 170, 174, 178, 182, 186, 295, 296, 398
<code>\@subtitle</code>	390, 391	<code>\tl_use:N</code>	501
<code>\@tempswatrue</code>	348	<code>\topmargin</code>	327
<code>\@thanks</code>	358, 381	<code>\toprule</code>	12
<code>\@title</code>	29, 388, 509	<code>\ttfamily</code>	1052
<code>\@titlepageiscoverpagefalse</code>	323		
<code>\@uppertitleback</code>	352	U	
<code>\cbx@margcitewrap</code>	1197, 1204, 1222	use commands:	
<code>\cbx@savdcites</code>	1195, 1199, 1201, 1212	<code>\use:N</code>	24
<code>\if@mainmatter</code>	581	<code>\usebibmacro</code>	1171, 1176, 1187, 1189, 1190, 1193, 1205, 1207, 1208, 1220
<code>\if@tempswa</code>	349	<code>\usekomafont</code>	388, 391, 395, 492
<code>\if@twoside</code>	347, 584, 590, 596	<code>\usemintedstyle</code>	12
<code>\l@lowertitleback</code>	5	<code>\usepackage</code>	7
<code>\next@tpage</code>	350		
<code>\par@updaterelative</code>	342, 370	V	
<code>\scr@ifundefinedorrelax</code>	552, 569, 619	<code>\version</code>	4, 144
<code>\titlepage@restore</code>	318, 324, 361	<code>\vfill</code>	354
<code>\z@</code>	342, 370	<code>\vsize</code>	322, 338
<code>\textbf</code>	235, 251, 259, 271, 506		
<code>\textemdash</code>	1108	W	
<code>\textheight</code>	331, 336, 337, 338	widowcontrol	14
<code>\textls</code>	537, 541	<code>\widowpenalty</code>	1102
<code>\textwidth</code>	330, 339, 340, 351, 355, 374, 408, 421, 434, 530		
<code>\the</code>	320, 321, 322, 517	X	
<code>\thechapter</code>	526	<code>\xappto</code>	1212
<code>\thefield</code>	1214	<code>\xetexengine</code>	10, 879, 894
<code>\thefootnote</code>	317		
<code>\theoremseparator</code>	657	Y	
<code>thesistype</code>	3	<code>\year</code>	517
<code>\thispagestyle</code>	343, 371		
<code>\title</code>	4, 21		
<code>\titlepagestyle</code>	313		
tl commands:			
<code>\tl_gset:Nn</code>	76, 78, 90, 92, 94, 96, 98, 99, 100, 102, 605, 770, 774, 778, 1003		